Direct Thermal POS Receipt Printer



Part Number/Price

Part #	Description	Est. Weight	Price
117233	TM-T88V, RS-232 and USB, PS-180 power supply	4 lb	Consult

Options/Accessories

Part #	Description	Price
23112	Power supply, PS-180	Consult
69917	One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 core 230 ft	Consult
83007	Parallel option connect-it cartridge	Consult
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	Consult
15547	Blunt end, 25-pin D-sub male RS-232 serial interface (Rice Lake indicators)	Consult
Consult	Custom RS-232 serial cable	Consult
79074	USB-A (male) to USB-B (male) cable, 6 ft	Consult
167545	TM88IV and V printhead	Consult

Standard Features

- High-speed printing of both text and graphics
- True grayscale image printing
- Convenient drop-in paper loading, auto cutter and status LEDs
- ENERGY STAR® qualified
- Accommodates 58 mm or 80 mm paper roll
- Paper saving print features
- Improved cover protects from dust and debris
- OS support for Microsoft® Windows® 7, Vista, XP, 2000; Mac OS X v10.4, v10.5, v10.6 (Power PC/ Intel Processor) and Linux

Specifications

Print Speed:

300 mm/s (11.81 inch/s)

Interface:

Built-in USB and serial interface (DB-25F); built-in USB and Ethernet: or built-in USB

Paper Dimensions:

80 mm: 3.13 × 3.27 in diameter 58 mm: 2.26 × 3.27 in diameter

Paper Thickness:

55 to 80 μm

Power:

24 VDC ± 7%

Temperature:
Operating: 31 °F to 113 °F (5 °C to 45 °C)
Storage: 14 °F to 122 °F (-10 °C to 50 °C)

Reliability: MTBF: 360,000 hours MCBF: 70 million lines

Dimensions:

(L x W x H) 7.68 × 5.71 × 5.83 in (195 × 145 × 148 mm)

Warranty:

One-year limited