

SINGLE POINT **RLFLS** Stainless Steel, Environmentally Sealed, Potted, IP67




Picture is a representation of actual product.

## **Order Information**

| Load Rating | Part # | Est. Weight | Price   |  |
|-------------|--------|-------------|---------|--|
| 50 lb       | 125612 | 3 lb        | Consult |  |
| Dimensions  | ·      |             |         |  |

| Rated Capacity | Α    | В    | С    | D    | E    | F    | Н    | J    | Т                  |
|----------------|------|------|------|------|------|------|------|------|--------------------|
| lb/in          |      |      |      |      |      |      |      |      |                    |
| 50             | 5.50 | 2.90 | 0.74 | 6.50 | 2.00 | 0.50 | 0.50 | 0.45 | 5/16-18 UNC x 0.50 |



## Interchangeable Products

AVERY WEIGH-TRONIX® FLS

## **Specifications**

Full Scale Output: 1.0 (± 10%) mV/V **Output Resistance:** 350 (± 3) ohm Input Resistance: 385 (± 10) ohm Material/Finish: Stainless steel **Temperature:** Operating range 0 °F to 150 °F (-18 °C to 65 °C) Seal Type: Environmentally sealed, IP67 Safe Overload: 150% full scale **Rated Excitation:** 5 to 15 VDC Hysteresis: 0.02% full scale Non-Linearity: 0.02% full scale **Insulation Resistance:** 5,000 megohm Cable Length: 10 ft Cable Color Code: Green +Excitation Black - Excitation Red +Signal White -Signal Warranty: Two-year limited

Ŕ

