

Printers

NEW Pricing

Prices printed in this catalog may no longer be valid for all products. Please visit www.ricelake.com or call 800-472-6703 for current pricing.

Table of Contents

Printers	861	DTL	884
<i>Rice Lake SURVIVOR® SST4®</i>	862	<i>Direct Thermal Label</i>	
<i>Washdown Label Printer</i>		DTL Plus/DTT	885
Rice Lake GUARDIAN™	863	<i>Direct Thermal Labels</i>	
<i>Stainless Steel Printer Enclosure</i>		DTL-SYN	885
Rice Lake GUARDIAN G-2™	863	<i>Direct Thermal Label</i>	
<i>Steel Printer Enclosure</i>		TTL	886
Rice Lake POLY GUARD	864	<i>Thermal Transfer Label</i>	
<i>Clear Printer Enclosure</i>		Fantastock	886
GoDEX® DT2x	865	<i>Thermal Transfer Label</i>	
<i>Direct Thermal Label Printer</i>		TTT Standard	887
GoDEX® DT4x+	866	SDR Super Durable Ribbon	887
<i>Direct Thermal Label Printer</i>		MaxWax™ GPR	888
GoDEX® G500	867	<i>General-Purpose Ribbon</i>	
<i>Direct Thermal/Thermal Transfer Label Printer</i>		Tape and Ticket Printer	
GoDEX® GX4000i Pro Series	868	Impact Ribbons	889
<i>Direct Thermal/Thermal Transfer Label Printer</i>		Tape Printer Paper Supplies	890
GoDEX® ZX1200i+	869	Electronic Scale Tickets	891
<i>Direct Thermal/Thermal Transfer Label Printer</i>		Mechanical Scale Tickets	892
GoDEX® ZX400i+ Series	870	<i>Create Your Own Custom Ticket</i>	
<i>Direct Thermal/Thermal Transfer</i>		Replacement Printheads	893
Honeywell® PD45S	871	Printer Cables	894
<i>Direct Thermal/Thermal Transfer Label Printer</i>		Printer Dust Covers	895
Honeywell® PM45	872		
<i>Direct Thermal/Thermal Transfer Label Printer</i>			
Honeywell® PX940	873		
<i>Direct Thermal/Thermal Transfer Label Printer</i>			
EPSON® TM-T88VI	874		
<i>Direct Thermal POS Receipt Printer</i>			
EPSON® TM-U220II	875		
<i>Tape Printer</i>			
EPSON® TM-U295	876		
<i>Ticket Printer</i>			
EPSON® TM-U590	877		
<i>Ticket Printer</i>			
Star® SP742	878		
<i>Dot Matrix Printers</i>			
Star® TSP 847	879		
<i>Receipt Thermal Printer</i>			
Star® TSP743 II	880		
<i>Direct Thermal Printer</i>			
Zebra® ZD411	881		
<i>Direct Thermal/Thermal Transfer Label Printer</i>			
Zebra® ZD421	882		
<i>Direct Thermal/Thermal Transfer Label Printer</i>			
Zebra® ZQ630	883		
<i>Direct Thermal Mobile Printer</i>			

Product names, logos, brands and other trademarks featured or referred to within this publication are the property of their respective trademark holders.

Rice Lake SURVIVOR® SST4®

Washdown Label Printer



Standard Features

- Washdown enclosure
- Direct thermal
- 203 dpi printhead
- Label length detection
- Real-time clock
- USB, serial or parallel communications
- Line mode

Options

- Thermal transfer
- Heater
- WPAN
- Wireless LAN (802.11 b/g/n)
- External label roll holder for 10 in (250 mm) OD label rolls
- External label rewinder
- Label dispenser and internal rewinder (factory installed)

Specifications

Print Speed:

10 in per second (254 mm)

Supply Roll Capacity:

8 in (203 mm) O.D. on
1.5 to 3.0 in (38 to 76 mm) core

Bar Code Modulus:

5 mil to 55 mil "X" dimension in picket fence or ladder orientations

Media Width:

4.09 in (104 mm)

Media Type:

Roll fed, die-cut or continuous labels; perforated or continuous tag/ticket stock

Print Length:

0.25 to 99 in (6 mm to 247 cm)

Media Thickness:

0.0025 to 0.0100 in (0.0635 to 0.254 mm)

1-D Bar Codes:

Code 39, Code 93, EAN 8/13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13 digit, Japanese Postnet, I 2 of 5 with human readable check digit, Standard 2 of 5, Industrial 2 of 5, Logmars, Code 11, Code 49, Cadablock

2-D Bar Codes:

PDF417, Micro PDF417, Datamatrix code, Maxicode, QR code, Micro QR code and Aztec code

Graphics Support:

PCX and BMP files

Memory:

128 MB FLASH
23 MB SDRAM

Dimensions:

(L x W x H) 24.5 x 12.5 x 15.0 in

Rating/Material:

IP69K, 304 stainless steel

Interfaces:

RS-232, USB, Ethernet TCP/IP

Power Source:

Switching power 100 to 240 VAC, 50/60 Hz input

Temperature:

Operating:
41 °F to 104 °F (5 °C to 40 °C)

Warranty:

One-year limited
Printhead (original):
One-year or 1 million linear inches
Printhead (replacement): 90 days

Part Number/Price

Part #	Description	Est. Weight	Price
209110	SST4 direct thermal	70 lb	\$5,753.00
209111	SST4 direct thermal with heater installed	70 lb	\$6,540.00
209112	SST4 direct thermal with Wi-Fi	70 lb	\$7,249.00
209113	SST4 direct thermal with Wi-Fi and heater installed	70 lb	\$8,003.00
209114	SST4 direct thermal with internal rewind	70 lb	\$6,369.00
209115	SST4 direct thermal with internal rewind and heater installed	70 lb	\$7,172.00
209116	SST4 direct thermal with internal rewind and Wi-Fi	70 lb	\$7,887.00
209117	SST4 direct thermal with internal rewind, Wi-Fi and heater installed	70 lb	\$8,689.00

Options/Accessories

Part #	Description	Price
111121	Heater kit for SST4 115 VAC (for installs after printer has been purchased)	\$730.00
111872	Heater kit for SST4, 230 VAC (for installs after printer has been purchased)	\$535.00
93181	Film, printhead cleaning 4 in wide, three/box	\$21.50
Label Stock/Ribbon (W x L)		
21776	Direct thermal, 3 x 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 x 6 in, 8 in diameter with perf., 1,000/roll	\$40.00/roll
25975	Direct thermal, 4.25 x 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 x 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 x 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
126629	Thermal kit, (4) 4 in labels, (2) 4 in ribbons and cleaning card	\$187.00
34056	Wax ribbon, black, 4 in, 1,182 ft (required for thermal transfer labels)	\$34.00/roll
Maintenance/Replacement Components		
209107	Printhead 203 dpi, SST4	\$260.00
209136	Board, main	\$345.00
209137	Power supply	\$235.00
209138	Display, front panel	\$245.00
209139	Power cord	\$15.00
Cables		
41276	DB9 male RS-232 serial data cable with blunt end (Rice Lake indicators)	\$77.00
64794	DB9 RS-232 serial data cable with DB9F to DB9M	\$69.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
Consult	Custom 20 mA/RS-232 serial interface cable	\$100.00

Custom cables are designed to interface with your specific equipment.
Please specify equipment model number and connector type.
Standard cable length is 5ft. \$2.00 charge for each additional foot.

Rice Lake GUARDIAN™

Stainless Steel Printer Enclosure



Standard Features

- Designed to protect various printers from harsh washdown environments
- Single lift-and-turn latch for easy access
- Adjustable anti-skid feet for easy leveling alignment and cleaning under unit
- Sliding label-access door
- Heavy-gauge 304 stainless steel construction for durability

Specifications

Enclosure:

Stainless steel; piano-style hinge

Dimensions:

(L x W x H)
21.25 x 14.25 x 14.25 in
(540 x 361 x 361 mm)

Warranty:

One-year limited

Part Number/Price

Part #	Description	Est. Weight	Price
66762	Guardian stainless steel printer enclosure. Consult for model compatibility	38lb	\$6,270.00

PRINTERS

Rice Lake GUARDIAN G-2™

Steel Printer Enclosure



Standard Features

- Designed to protect various printers from harsh washdown environments
- Single lift-and-turn latch for easy access
- Adjustable anti-skid feet for easy leveling alignment and cleaning under unit
- Sliding label-access door
- Heavy-gauge 304 stainless steel construction for durability

Specifications

Enclosure:

304 stainless steel

Dimensions:

(L x W x H)
18.50 x 12.75 x 8.25 in
(324 x 209.5 x 469.9 mm)

Warranty:

One-year limited

Part Number/Price


Part #	Description	Est. Weight	Price
78672	Guardian G-2, 8.44 x 6.54 in	30lb	\$1,331.00
99465	Guardian G-2, 7.23 x 6.52 in	30lb	\$1,331.00
107638	Guardian G-2, 7.41 x 6.54 in	30lb	\$1,331.00
107639	Guardian G-2, 10.22 x 9.10 in	30lb	\$1,331.00

Options/Accessories

Part #	Description	Price
46341	Heater option	\$248.00
46342	Fan option	\$132.00

Rice Lake POLY GUARD

Clear Printer Enclosure



Standard Features

- Designed for use in meat and food processing plants
- Cover separates from bottom
- Power and data cable feed through sealed notch in back of enclosure
- Side door for easy label loading

Specifications

Enclosure:

0.25 in polycarbonate
Base-natural polyethylene (butcher's block)

Dimensions:

(L x W x H)
24.50 × 14.00 × 14.75 in
Add 0.50 in sides for latches and 0.50 in side door

Warranty:

90-day limited

Part Number/Price

Part #	Description	Est. Weight	Price
88532	Enclosure, GoDEX 1200i+	24 lb	\$1,683.00
Consult	Additional models available	24 lb	Consult

Options/Accessories

Part #	Description	Price
Consult	Ventilation fan	Consult
Consult	Heater assembly with power	Consult

PRINTERS



Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL
- 203 dpi
- 32-bit CPU
- Drop-in media loading
- USB or RS-232 interface (DB-9F)
- Plain, gap label, black, mark or fanfold label
- Label length detection
- Direct thermal
- Serrated tear bar

Specifications

Print Speed:

Up to 7 ips

Print Length:

Min: 0.16 in

Max: 68 in

Print Width:

2.12 in

Media:

Types: Continuous form, gap labeling, black mark

sensing and punched sensing

Thickness: Min. 0.0024 in - Max. 0.01 in

Label Roll Diameter: Max. 5 in

Core Diameter: Min. 1 in - Max. 1.5 in

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions

11 resident alphanumeric fonts (included OCR A and B) are expandable eight times horizontally and vertically

1-D Bar codes:

China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/ EAN -13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5, Interleaved 2-of-5 (I 2 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K-Mart, Random Weight and Pharmacode

2-D Bar codes:

Aztec code, Code 49, Codablock F, Datamatrix code, Maxi Code, Micro PDF417, Micro QR code, PDF417, QR code, TLC 39, GS1 Composite, Dot Code, Macro PDF417

Memory:

4 MB flash

Interfaces:

USB 2.0 (Type B)

Serial Port (RS-232)

Ethernet 10/100 Mbps

Power:

Auto Switching 100/240 VAC, 50/60 Hz

Temperature:

Operating:

41 °F to 104 °F (5 °C to 40 °C)

Storage:

-4 °F to 122 °F (-20 °C to 50 °C)

Dimensions:

(L x W x H)

8.58 x 3.94 x 6.77 in

(218 x 100 x 172 mm)

Warranty:

Two-year limited

Approvals:

CE Listed

FCC Class A

cULus Listed

Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
167515	DT2x 2 in direct thermal, time and date 10/240 VAC printer	3 lb	\$365.00
167626	Label peeler, black	—	\$41.00
167627	Cutter, black	—	\$210.00
107532	Printhead	—	\$120.00

Options/Accessories

Part #	Description	Price
38941	Cleaning pen for open printhead printers 12/box	\$67.00
111085	Power supply, printers	\$170.00
15438	Power cord, detachable	\$35.00

Label Stock/Ribbon

110347	Direct thermal, (W x L) 2.25 x 1.25 in, 5 in diameter with perf., 2,100/roll	\$17.00/roll
40332	Direct thermal, (W x L) 2.25 x 2 in, 5 in diameter with perf., 1,445/roll	\$19.00/roll
110348	Direct thermal, (W x L) 2.25 x 3 in, 5 in diameter with perf., 950/roll	\$18.00/roll
110349	Direct thermal, (W x L) 2.25 x 4 in, 5 in diameter with perf., 700/roll	\$17.00/roll
65617	Direct thermal, (W x L) 2.25 x 4.5 in, 5 in diameter with perf., 600/roll	\$19.00/roll
110346	Direct thermal, (W x L) 1.20 x 0.85 in, 5 in diameter with perf., 2,710/roll	\$17.00/roll
47761	Direct thermal, (W x L) 2.5 x 121 ft, continuous 12 rolls/case	\$106.00/case

Cables

41276	6 ft serial cable DB9 M to blunt end (Rice Lake indicators)	\$77.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
64661	6 ft serial cable DB9 M to 8-Pin DIN	\$69.00
64660	6 ft serial cable DB9 M to DB9 male	\$69.00
Consult	Custom RS-232 serial cable	\$100.00



GoDEX® DT4x+

Direct Thermal Label Printer



Approvals



Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL or Q-Label
- 203 dpi
- 32-bit CPU
- Drop-in media loading
- USB, Ethernet and RS-232 interface
- Plain, gap label, black, mark or fanfold label
- Label length detection

Part Number/Price

Part #	Description	Est. Weight	Price
167516	DT4x+ 4 in direct thermal, 110/240 VAC printer	4 lb	\$446.00
167628	Label peeler, black	—	\$57.50
167629	Cutter, black	—	\$210.00
150743	Printhead	—	\$205.00
107638	Guardian enclosure	—	\$1,331.00

Options/Accessories

Part #	Description	Price
38941	Cleaning pen for open printhead printers 12/box	\$67.00
111085	Power supply, printers	\$170.00
15438	Power cord, detachable	\$35.00
193466	Real-time clock for DT4xW	\$21.00

Label Stock/Ribbon

53251	Direct thermal, (W × L) 4 × 3 in, 5 in diameter with perf., 930/roll	\$35.00/roll
40331	Direct thermal, (W × L) 4 × 4 in, 5 in diameter with perf., 745/roll	\$37.00/roll
37345	Direct thermal, (W × L) 4 × 6 in, 5 in diameter with perf., 450/roll	\$26.00/roll

Cables

41276	6 ft serial cable DB9 M to blunt end (Rice Lake indicators)	\$77.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
64661	6 ft serial cable DB9 M to 8-Pin DIN	\$69.00
64660	6 ft serial cable DB9 M to DB9 male	\$69.00
Consult	Custom RS-232 serial cable	\$100.00

Specifications

Print Speed:

Up to 7 ips

Print Length:

Min: 0.16 in

Max: 68 in

Print Width:

4.25 in

Media:

Types: Continuous form, gap labeling, black mark sensing and punched sensing

Thickness: Min. 0.0024 in - Max. 0.008 in

Label Roll Diameter: Max. 5.0 in

Core Diameter: Min. 1 in, Max. 1.5 in

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions

11 resident alphanumeric fonts (included OCR A and B) are expandable eight times horizontally and vertically

Printer Language:

EZPL, GEPL, GZPL, GDPL auto switch

Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C,) UCC/EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 and 5) 2 of 5, EAN 8/13 (add on 2 and 5) Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

Memory:

8 MB flash

Interfaces:

USB 2.0 (Type B)

Serial Port (RS-232)

Ethernet 10/100 Mbps

Power:

Auto Switching 100 to 240 VAC, 50/60 Hz

Temperature:

Operating:

41 °F to 104 °F (5 °C to 40 °C)

Storage:

-4 °F to 122 °F (-20 °C to 50 °C)

Dimensions:

(L × W × H)

8.58 × 6.61 × 6.53 in

(218 × 168 × 166 mm)

Warranty:

Two-year limited

Approvals:

CE Listed

FCC Class A

cULus Listed



Approvals



Standard Features

- Auto language emulations GEPL, GZPL
- Free GoLabel design software for EZPL or Q Label
- 203 dpi
- 32-bit CPU
- Drop-in media loading
- USB or RS-232 (DB-9F) interface
- Plain, gap label, black, mark or fanfold label
- Label length detection

Part Number/Price

Part #	Description	Est. Weight	Price
132425	G500 4 in direct/thermal transfer, 110/240 VAC printer	6 lb	\$677.00
150744	Label peeler, black	—	\$42.00
150745	Cutter	—	\$450.00
150746	Printhead	—	\$205.00
107639	Guardian enclosure	—	\$1,331.00

Options/Accessories

Part #	Description	Price
38941	Cleaning pen for open printhead printers 12/box	\$67.00
111085	Power supply, printers	\$170.00
15438	Power cord, detachable	\$35.00
Label Stock/Ribbon		
53261	Thermal transfer, (W × L) 4 × 3 in, 5 in diameter with perf., 930/roll	\$32.00/roll
178965	Ribbon (black), 4.3 in wax/resin, 984 ft length	\$33.00/roll
Cables		
41276	6 ft serial cable DB9 M to blunt end (Rice Lake indicators)	\$77.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
64661	6 ft serial cable DB9 M to 8-Pin DIN	\$69.00
64660	6 ft serial cable DB9 M to DB9 male	\$69.00
Consult	Custom RS-232 serial cable	\$100.00

Specifications

Print Speed:

Up to 5 ips

Print Length:

Min: 0.16 in

Max: 68 in

Print Width:

4.25 in

Media:

Types: Continuous form, gap labeling, black mark sensing and punched sensing

Thickness: Min. 0.0024 in - Max. 0.008 in

Label Roll Diameter:

Max. 5.0 in

Core Diameter: Min. 1 in - Max. 1.5 in

Printer Language:

GZPL or GEPL, EZ PL auto switch

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions

11 resident alphanumeric fonts (included OCR A and B) are expandable eight times horizontally and vertically

Bar Codes:

Code 39, Code 93, Code 128 (subset A, B, C), UCC/EAN - 128 K-Mart, UCC/EAN - 128, UPC A/E (add on 2 and 5), 2 of 5, EAN 8/13 (add on 2 and 5), Codabar, Post Net, EAN 128, DUN 14, MaxiCode, HIBC, Plessey, Random Weight, Telepen, FIM, China Postal Code, RPS 128, PDF 417, Datamatrix code, QR Code

Memory:

8 MB flash

Interfaces:

USB 2.0 (Type B)

Serial Port (RS-232)

Ethernet (RJ-45)

Power:

Auto Switching 100/240 VAC, 50/60 Hz

Temperature:

Operating: 41 °F to 104 °F (5 °C to 40 °C)

Storage: -4 °F to 122 °F (-20 °C to 50 °C)

Dimensions:

(L × W × H)

11.2 × 8.9 × 6.8 in

(285 × 226 × 171 mm)

Warranty:

Two-year limited

Approvals:

CE Listed

FCC Class A

GoDEX® GX4000i Pro Series

Direct Thermal/Thermal Transfer Label Printer



Approvals



Standard Features

- Built in video assist guidance
- Free GoLabel and GoLabel II design software
- 32-bit RISC CPU
- Equipped with a 5 in LCD touchscreen
- Aluminum cast frame

Part Number/Price

Part #	Description	Est. Weight	Price
GX4200i			
222248	Printer, Label GX4200i, 203 dpi, 5 inch color touchscreen	30 lb	\$2,899.00
GX4300i			
222250	Printer, Label GX4300i, 300 dpi, 5 inch color touchscreen	30 lb	\$3,020.00

Options/Accessories

Part #	Description	Price
225332	Wi-Fi module	\$275.00
Label Stock/Ribbon (W × L)		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 × 6 in, 6 in diameter with perf., 1,000/roll	\$40.00/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
34056	Ribbon, black, 4 in, 1,181 ft, wax	\$34.00/roll
126629	Thermal kit, (4) 4 × 4 in labels, (2) 4 in ribbons and 1 cleaning card	\$187.00
Cables		
41276	DB9 male RS-232 serial data cable with blunt end (Rice Lake indicators)	\$77.00
64794	DB9 RS-232 serial data cable with DB9F to DB9M	\$69.00
37527	6 ft parallel cable	\$37.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
Printheads		
225309	Printhead, 203 dpi	\$347.00
225310	Printhead, 300 dpi	\$495.00

Specifications

Print Speed:

GX4200i: up to 16 ips
GX4300i: up to 12 ips

Print Width:

4.09 in

Print Length:

GX4200i: 0.16 to 279.53 in
GX4300i: 0.16 to 125.98 in

Media:

Types: Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
Thickness: Min. 0.0024 in - Max. 0.01 in
Label Roll Diameter: Max. 8 in
Core Diameter: Min. 1.5 in - Max. 3 in

Printer Language:

EZPL, GEPL, GZPL, GDPL auto switch

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions
TTF fonts: (Bold / Italic / Underline) 0°, 90°, 180°, 270° rotatable
Internal TTF Fonts x 5: Traditional Chinese, Simplified Chinese, Japanese, Korean, Western languages

1-D Bar Codes:

China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/ EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5, Interleaved 2-of-5 (1 of 2 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K-Mart, Random Weight and Pharmacode

2-D Bar Codes:

Aztec code, Code 49, Codablock F, Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR Code, TLC 39, GS1 Composite, DotCode, Marco PDF 417

Memory:

256 MB flash; 256 MB SDRAM

Interfaces:

USB 2.0 (Type B)
Serial Port (RS-232)
Ethernet 10/100 Mbps
USB Host (A-Type)

Power:

Auto Switching 100 to 240 VAC, 50/60 Hz

Resolution:

GX4200i: 203 dpi
GX4300i: 300 dpi

Temperature:

Operating: 41 °F to 104 °F (5 °C to 40 °C)
Storage: -4 °F to 140 °F (-20 °C to 60 °C)

Dimensions:

(L × W × H)
18 × 11 × 12 in
(460 × 269 × 309 mm)

Warranty:

Five-year limited

Approvals:

CE Listed
FCC Class B
cULus Listed



Approvals



Standard Features

- Auto language emulations GDPL
- Free GoLabel design software for EZPL
- 32-bit MPU
- All-metal frame structure
- Various output options
- Supports high-volume printing jobs
- Full range adjustable media sensors

Part Number/Price

Part #	Description	Est. Weight	Price
209082	Printer, Label ZX1200i+ 203 dpi, color touchscreen	30 lb	\$2,200.00
209083	Printer, Label ZX1300i+ 300 dpi, color touchscreen	30 lb	\$2,530.00
209084	Printer, Label ZX1200i+ 203 dpi, color touchscreen with internal rewind	30 lb	\$2,530.00
209085	Printer, Label ZX1200i+ 203 dpi, color touchscreen with internal rewind, and Wi-Fi	30 lb	\$2,750.00

Options/Accessories

Part #	Description	Price
225332	Wi-Fi module	\$275.00
Label Stock/Ribbon (W × L)		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 × 6 in, 6 in diameter with perf., 1,000/roll	\$40.00/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
34056	Ribbon, black, 4 in, 1,181 ft, wax	\$34.00/roll
126629	Thermal kit, (4) 4 × 4 in labels, (2) 4 in ribbons and 1 cleaning card	\$187.00
Cables		
41276	DB9 male RS-232 serial data cable with blunt end (Rice Lake indicators)	\$77.00
64794	DB9 RS-232 serial data cable with DB9F to DB9M	\$69.00
37527	6 ft parallel cable	\$37.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
Printheads		
209107	Printhead, 203 dpi	\$260.00

Specifications

Print Speed:

Up to 10 ips

Print Length:

Min: 0.16 in
Max: 279.53 in

Print Width:

4.09 in

Media:

Types: Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
Thickness: Min. 0.0024 in - Max. 0.01 in
Label Roll Diameter: Max. 8 in
Core Diameter: Min. 1.5 in - Max. 3 in

Printer Language:

EZPL, GEPL, GZPL, GDPL auto switch

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions
TTF fonts: (Bold/Italic/Underline) 0°, 90°, 180°, 270° rotatable
internal TTF fonts x 5: traditional Chinese, simplified Chinese, Japanese, Korean, western languages

1-D Bar Codes:

China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/ EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5, Interleaved 2-of-5 (1 2 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K-Mart and Random Weight

2-D Bar Codes:

Aztec code, Code 49, Codablock F, Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR code, TLC 39, GS1 Composite

Memory:

256 MB flash

Interfaces:

USB 2.0 (Type B)
Serial Port (RS-232)
Ethernet 10/100 Mbps
USB Host (A-Type)

Power:

Auto Switching 100/240 VAC, 50/60 Hz

Resolution:

ZX1200i+: 203 dpi
ZX1300i+: 300 dpi

Temperature:

Operating: 41 °F to 104 °F (5 °C to 40 °C)
Storage: -4 °F to 140 °F (-20 °C to 60 °C)

Dimensions:

(L × W × H)
18.3 × 10.6 × 12.3 in
(465 × 269 × 312 mm)

Warranty:

Three-year limited

Approvals:

CE
FCC Class B
cULus Listed

GoDEX® ZX400i+ Series

Direct Thermal/Thermal Transfer



Approvals



Standard Features

- Free GoLabel II design software
- Auto language emulations GDPL
- 32-bit RISC CPU
- Die-cast frame

Part Number/Price

Part #	Description	Est. Weight	Price
ZX420i+			
222252	Printer, Label ZX420i+ 203 dpi, DT, TT, 6 IPS, USB, RS232, Ethernet, Color screen with navigation buttons	24 lb	\$1,062.00
ZX430i+			
222253	Printer, Label ZX430i+ 300 dpi, DT, TT, 4 IPS, USB, RS232 Ethernet, Color Screen with push button navigation	24 lb	\$1,144.00

Options/Accessories

Part #	Description	Price
Label Stock/Ribbon (W × L)		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 × 6 in, 6 in diameter with perf., 1,000/roll	\$40.00/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
34056	Ribbon, black, 4 in, 1,181 ft, wax	\$34.00/roll
126629	Thermal kit, (4) 4 × 4 in labels, (2) 4 in ribbons and 1 cleaning card	\$187.00
Cables		
41276	DB9 male RS-232 serial data cable with blunt end (Rice Lake indicators)	\$77.00
64794	DB9 RS-232 serial data cable with DB9F to DB9M	\$69.00
37527	6 ft parallel cable	\$37.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
Printheads		
225395	Printhead, 203 dpi	\$275.00
225396	Printhead, 300 dpi	\$385.00

Specifications

Print Speed:

ZX420i+: Up to 6 ips
ZX430i+: Up to 4 ips

Print Width:

ZX420i+: 4.25 in
ZX430i+: 4.16 in

Print Length:

ZX420i+: 0.16 to 279.53 in
ZX430i+: 0.16 to 125.98 in

Media:

Types: Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming
Thickness: Min. 0.0024 in - Max. 0.01 in
Label Roll Diameter: Max. 8 in
Core Diameter: Min. 1 in - Max. 3 in

Printer Language:

EZPL, GEPL, GZPL, GDPL auto switch

Resident Fonts:

Bitmap fonts 8 times expandable in horizontal and vertical directions
TTF fonts: (bold/italic/underline) 0°, 90°, 180°, 270° rotatable
Internal TTF fonts x 5: Traditional Chinese, Simplified Chinese, Japanese, Korean, Western languages

1-D Bar Codes:

China Postal Code, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5, Interleaved 2-of-5 (1 2 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT 128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K Mart, Random Weight and Pharmacode

2-D Bar Codes:

Aztec code, Code 49, Codablock F, Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417, QR code, TLC 39, GS1 Composite, DotCode, Marco PDF 417

Memory:

128 MB flash; 128 MB SDRAM

Interfaces:

USB 2.0 (Type B)
Serial Port (RS-232)
Ethernet 10/100 Mbps
USB Host (A-Type)

Power:

Auto Switching 100 to 240 VAC, 50/60 Hz

Resolution:

ZX420i+: 203 dpi
ZX430i+: 300 dpi

Temperature:

Operating: 41 °F to 104 °F (5 °C to 40 °C)
Storage: -4 °F to 140 °F (-20 °C to 60 °C)

Dimensions:

(L × W × H)
15.9 × 10.2 × 10.8 in
(403 × 260 × 274 mm)

Warranty:

Three-year limited

Approvals:

CE
FCC Class B
cULus Listed

Honeywell® PD45S

Direct Thermal/Thermal Transfer Label Printer



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
209079	Label printer, PD45S thermal transfer, 203 dpi, 115/230 VAC Requires power cord 15438 (sold separately)	27 lb	\$2,420.00
209080	Label printer, PD45S thermal transfer, 203 dpi, 115/230 VAC, with peel and present, internal rewind Requires power cord 15438 (sold separately)	27 lb	\$3,025.00
209081	Label printer, PD45S thermal transfer, 300 dpi, 115/230 VAC, with peel and present, internal rewind Requires power cord 15438 (sold separately)	27 lb	\$3,146.00

Options/Accessories

Part #	Description	Price
15438	US power cord	\$35.00
35664	Pre-saturated cleaning cards, 4 x 6 in 25/box	\$60.00
93181	Film, printhead cleaning 4 in wide, 3/box	\$21.50
Label Stock/Ribbon (W x L)		
21776	Direct thermal, 3 x 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 x 6 in, 6 in diameter with perf., 1,000/roll	\$40.00/roll
25975	Direct thermal, 4.25 x 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 x 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 x 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
34056	Ribbon, black, 4 in, 1,181 ft, wax	\$34.00/roll
126629	Thermal kit, (4) 4 x 4 in labels, (2) 4 in ribbons and 1 cleaning card	\$187.00
Cables		
41276	DB9 male RS-232 serial data cable with blunt end (Rice Lake indicators)	\$77.00
64794	DB9 RS-232 serial data cable with DB9F to DB9M	\$69.00
37527	6 ft parallel cable	\$37.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
Printheads		
209251	Printhead 203 dpi	\$685.00
209252	Printhead 300 dpi	\$758.00

Standard Features

(REPLACING M-CLASS PRINTERS)

- 203 dpi or 300 dpi
- Serial, USB, wired TCP/IP
- Real-time clock
- Color graphical display

Specifications

Print Speed:

203 dpi: 2 to 10 ips
300 dpi: 2 to 8 ips

Print Length:

0.25 to 99 in (6 to 2,475 mm)

Supply Roll Capacity:

8 in (203 mm) OD on 1.5 to 3.0 in
(38 to 76.2 mm) cores
Fanfold stock accepted from rear and
bottom of printer

Bar Code Modulus:

5 to 55 mil "X" dimension in picket fence
or ladder orientations

Media Width:

0.75 to 4.5 in (17 to 114 mm)

Media Type:

Roll fed or fan-fold materials, die-cut or continuous
labels; perforated or continuous tag/ticket stock

Media Thickness:

0.0025 to .01 in (0.0635 to 0.254 mm)

Ribbons:

Industry standard ribbon widths: 1 in (25 mm)
Ribbon core: 1,476 ft (450 m) in length

Bar Codes:

Code 3 of 9, UPC-A, UPC-E, Interleaved
2 of 5, Code 128, EAN-8, EAN-13, HIBC,
Codabar, Plessey, UPC 2 and 5 digit
addendums, Code 93, Postnet, UCC/EAN Code
128, Telepen, UPS MaxiCode, FIM, PDF417, USD-8,
Datamatrix, QR Code, Aztec,
TLC 39, Micro PDF417, RSS

Graphics Support:

.PCX, .BMP and .IMG files

Memory:

128 MB RAM

Power Source:

Auto-sensing 90 to 132 VAC/180 to 264 VAC
47 /63 Hz

Temperature:

Operating:
40 °F to 95 °F (4 °C to 35 °C)

Dimensions:

(L x H x W)
17.24 x 10.63 x 9.80 in

Warranty:

One-year limited
Printhead (original):
One-year or 1 million linear inches
Printhead (replacement): 90 days

Approvals:

CE Listed
FCC
UL Listed
CSA

PRINTERS

Honeywell® PM45

Direct Thermal/Thermal Transfer Label Printer



Icon LED version
(no display)

Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
208559	PM45A, icon display, Ethernet, fixed hanger, DT, 203 dpi, US power cord	51 lb	\$3,262.00
208560	PM45A, icon display, Ethernet, fixed hanger, TT, 203 dpi, US power cord	51 lb	\$2,607.00
208561	PM45A, full touch display, Ethernet, fixed hanger, TT, 203 dpi, US power cord	51 lb	\$3,049.00
208562	PM45A, full touch display, Ethernet, fixed hanger, rewinder + label taken sense, TT, 203 dpi, US power cord	51 lb	\$3,472.00
208563	PM45A, full touch display, Ethernet, Bluetooth®, Wi-Fi NA, fixed hanger, TT, 203 dpi, US power cord	51 lb	\$3,465.00
208564	PM45A, icon display, Ethernet, fixed hanger, TT, 300 dpi, US power cord	51 lb	\$3,557.00
208565	PM45A, full touch display, Ethernet, fixed hanger, TT, 300 dpi, US power cord	51 lb	\$3,705.00
208566	PM45A, full touch display, Ethernet, fixed hanger, rewinder + label taken sense, TT, 300 dpi, US power cord	51 lb	\$4,010.00
208567	PM45A, full touch display, Ethernet, Bluetooth®, Wi-Fi NA, fixed hanger, TT, 300 dpi, US power cord	51 lb	\$4,446.00

Options/Accessories

Part #	Description	Price
207889	Honeywell® WLAN 802.11 option card	\$530.00
68517	External rewinder/unrewinder DMX	\$495.00
214842	Standard cutter kit for 10 mil stock	\$1,104.00
Label Stock/Ribbon (W × L)		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 × 6 in, 8 in diameter with perf., 1,000/roll	\$40.00/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
126629	Thermal kit, (4) 4 × 4 in labels, (2) 4 in ribbons and 1 cleaning card	\$187.00
34056	Ribbon (black), 4 in, 1,181 ft, wax	\$34.00/roll
Cables		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
41276	DB9M cable to blunt end, 9-pin (Rice Lake indicators)	\$77.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
64794	DB9F to DB9M RS-232 cable	\$69.00
Printheads		
211645	Printhead, 203 dpi	\$825.00
211646	Printhead, 300 dpi	\$826.00

Standard Features

(REPLACING I-CLASS PRINTERS)

- Two types of user interfaces, touchscreen display or icon LEDs (no display)
- PrintSet MC support for systems settings and configuration (required for Icon LED model)
- Opintel support for print optimization and firmware upgrades
- Smart Media calibration detects printing method, media type and length
- Enhance security with secured flashing
- Internal rewinder
- Label tear sensor
- Larger ribbon collapsible core for easy ribbon removal
- Ethernet/USB/serial
- USB host port for connecting storage devices, scanners, or keyboards
- USB device port to connect to a PC
- Wide range of printer accessories
- US power cord

Specifications

Print Speed:

203 dpi: 2 to 14 ips
300 dpi: 2 to 12 ips

Print Length:

0.25 to 99 in (6 to 247 mm)

Supply Roll Capacity:

Maximum 8.375 in diameter on 3 in core

Media Width:

0.79 to 4.5 in

Media Type:

Tag, label, ribbon

Media Thickness:

0.003 to 0.01 in

Ribbons (Optional):

2 in core, up to 4.33 in wide

Printer Command Language:

WMS, FP, DPL, IPL, ZPL II, XML, DP

Bar Codes:

SCC-14, HIBC 39, EAN-13, HIBC 128, ITF-14, EAN-128, GS1 Databar Expanded, ISBT 128, Code 39, EAN-8, Code 128, GS1-128, UPC-E, UPC-A, Interleaved 2 of 5, RSS14E, ISBT Data Matrix, Data Matrix

Graphics Support:

PNG, GIF, PCX, BMP

Memory:

256 MB Flash/1 GB Ram

Interfaces:

USB 2.0 Host (x2), USB 2.0 Device, Ethernet 10/100 Mbps, RS-232 (up to 115.2 KB/s)

Power Source:

100 to 240 VAC, 50/60 Hz

Temperature:

Operating:
41 °F to 104 °F (5 °C to 40 °C)

Dimensions:

(L × W × H)
19.0 × 11.2 × 11.6 in

Warranty:

One-year limited
Printhead (original):
One-year or 1 million linear inches
Printhead (replacement): 90 days

Approvals:

CE Listed
UL Listed

Honeywell® PX940

Direct Thermal/Thermal Transfer Label Printer



Standard Features

(REPLACING H-CLASS PRINTERS)

- Full-touch display
- Internal rewinder
- US power cord
- Ethernet/USB/serial
- Label tear sensor

Specifications

Print Speed:

203 dpi: 2 to 14 ips
300 dpi: 2 to 12 ips

Print Length:

0.25 to 99 in (6 to 247 mm)

Supply Roll Capacity:

Maximum 8.375 in diameter on 3 in core

Media Width:

0.79 to 4.5 in

Media Type:

Tag, label, ribbon

Media Thickness:

0.003 to 0.01 in

Ribbons (Optional):

2 in core, up to 4.33 in wide

Printer Command Language:

WMS, FP, DPL, IPL, ZPL II, XML, DP

Bar Codes:

SCC-14, HIBC 39, EAN-13, HIBC 128, ITF-14, EAN-128, GS1 Databar Expanded, ISBT 128, Code 39, EAN-8, Code 128, GS1-128, UPC-E, UPC-A, Interleaved 2 of 5, RSS14E, ISBT Data Matrix, Data Matrix

Graphics Support:

PNG, GIF, PCX, BMP

Memory:

256 MB flash / 1 GB ram

Interfaces:

USB 2.0 Host (x2), USB 2.0 Device, Ethernet 10/100 Mbps, RS-232 (up to 115.2 KB/s)

Power Source:

100 to 240 VAC, 50/60 Hz

Temperature:

Operating:
41 °F to 104 °F (5 °C to 40 °C)

Dimensions:

(L × W × H)
15.70 × 10.25 × 19.92 in

Warranty:

One-year limited on parts
One-year or 1 million linear inches on original printhead

Part Number/Price

Part #	Description	Est. Weight	Price
207885	Label printer, PX940 direct thermal/thermal transfer 203 dpi	51 lb	\$4,399.00
207886	Label printer, PX940 direct thermal/thermal transfer 300 dpi	51 lb	\$4,727.00

Options/Accessories

Part #	Description	Price
207889	Honeywell® WLAN 802.11 option card	\$530.00
68517	External rewinder/unrewinder DMX	\$495.00
Label Stock		
21776	Direct thermal, 3 × 3 in, 8 in diameter with perf., 2,000/roll	\$77.00/roll
150921	Direct thermal, 4 × 6 in, 6 in diameter with perf., 460/roll	\$40.00/roll
25975	Direct thermal, 4.25 × 2.5 in, 6 in diameter with perf., 1,095/roll	\$34.00/roll
21788	Thermal transfer, 4 × 6 in, 8 in diameter, 1,000/roll	\$24.00/roll
20573	Thermal transfer, 4 × 6.5 in, 8 in diameter, 900/roll	\$25.00/roll
126629	Thermal kit, (4) 4 in labels, (2) 4 in ribbons and 1 cleaning card	\$187.00
34056	Ribbon (black), 4 in, 1,181 ft wax	\$34.00/roll
Cables		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
41276	DB9M cable to blunt end, 9-pin (Rice Lake indicators)	\$77.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
64794	RS-232 DB9FM/M null modem	\$69.00
Printheads		
207887	Printhead 203 dpi	\$840.00
207888	Printhead 300 dpi	\$961.00

PRINTERS

EPSON® TM-T88VI

Direct Thermal POS Receipt Printer



Standard Features

- High-speed printing of both text and graphics
- True grayscale image printing
- Convenient drop-in paper loading, auto cutter and status LEDs
- ENERGY STAR® qualified
- Accommodates 58 mm or 80 mm paper roll
- Paper saving print features
- Improved cover protects from dust and debris
- OS support for Microsoft® Windows® 7, Vista, XP, 2000; Mac OS X v10.4, v10.5, v10.6 (Power PC/ Intel Processor) and Linux

Specifications

> Print Speed:

300 mm/s (11.81 inch/s)

Interface:

Built-in USB and serial interface (DB-25F);
built-in USB and Ethernet: or built-in USB

Paper Dimensions:

80 mm: 3.13 × 3.27 in diameter
58 mm: 2.26 × 3.27 in diameter

Paper Thickness:

55 to 80 µm

Power:

24 VDC ± 7%

Temperature:

Operating: 31 °F to 113 °F (5 °C to 45 °C)
Storage: 14 °F to 122 °F (-10 °C to 50 °C)

Reliability:

MTBF: 360,000 hours
MCBF: 70 million lines

Dimensions:

(L × W × H)
7.68 × 5.71 × 5.83 in
(195 × 145 × 148 mm)

Warranty:

One-year limited

Part Number/Price

Part #	Description	Est. Weight	Price
117233	TM-T88V, RS-232 and USB, PS-180 power supply	4 lb	\$715.00

Options/Accessories

Part #	Description	Price
23112	Power supply, PS-180	\$132.00
69917	One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 core 230 ft	\$6.00
83007	Parallel option connect-it cartridge	\$73.00
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	\$70.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface (Rice Lake indicators)	\$70.00
Consult	Custom RS-232 serial cable	Consult
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
167545	TM88IV and V printhead	\$135.00

PRINTERS



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
232439	TM-U220IID RS232 Serial, Universal Power Supply	10 lb	\$495.00
232440	TM-U220 IIB USB, Universal Power Supply	10 lb	\$480.00
232441	TM-U220IIB Ethernet, Universal Power Supply	10 lb	\$726.00

Options/Accessories

Part #	Description	Price
83007	Parallel option connect-it cartridge	\$73.00
35666	Protective dust cover	\$63.00
31296	Ink cartridge (purple)	\$12.75
66499*	Ink cartridge (black and red)	\$12.75
69916	One-ply bond paper roll, (W × L) 3 in × 150 ft (76 mm × 46 m) 3 in OD	\$5.25/roll
69915	Two-ply bond paper roll, (W × L) 3 in × 90 ft (76 mm × 28 m), white/canary yellow 3 in OD	\$7.50/roll
35667	Additional operating manual	\$17.00
72309	Power supply, 12 VDC vehicle cigarette plug	\$290.00
23112	115 VAC power supply (included with printer)	\$132.00
Cables		
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	\$70.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00

Interfaces to: Rice Lake indicators with a serial port screw terminal connection. Consult custom 20mA/RS-232 serial interface cable \$100.00. Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type. Standard cable length is 5ft. \$2.00 charge for each additional foot.

*Red/Black ribbon to turn on ASCII code-27,114,48 ON 27,114,49 OFF

Standard Features

- Nine-pin dot matrix printhead
- High-speed printing
- Drop-in paper set and auto paper loading
- Automatically transmits changes in printer status
- Optional connect-it cartridges for parallel, USB, 10 Base-T
- Uses MI88D mechanism

Specifications

Print Speed:

Approx. 4.7 lines per seconds

Characters Per Line:

40 characters

Form Thickness:

0.002 to 0.003 in (0.06 to 0.09 mm)

Ribbon:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints) Black ink also available

Serial Interfaces:

Baud rates: 4800, 9600
RS-232 compatible (DB-25F) or USB model

Parity:

7 or 8 bits, none, even or odd

Temperature:

Operating:
32 °F to 122 °F (0 °C to 50 °C)

Dimensions:

(L × W × H)
Type A: 11.30 × 6.30 × 6.20 in
(286 × 160 × 158 mm)
Type D: 9.70 × 6.30 × 5.40 in
(248 × 160 × 139 mm)

Warranty:

Two-year limited
(includes printhead)

Approvals:

CE Listed
UL Listed
CSA

EPSON® TM-U295

Ticket Printer



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
23113	TM-U295 ticket printer, 115/230 VAC with power supply, cool white	9 lb	\$693.00
35891	TM-U295 ticket printer, 115/230 VAC with power supply, 25 DB to blunt end cable, cool white	9 lb	\$748.00
33816	TM-U295 ticket printer, 24 VDC, cool white	9 lb	\$655.00

Options/Accessories

Part #	Description	Price
29582	Protective dust cover	\$58.00
29584	Ink cartridge (purple) ERC-27	\$12.75
29583	Ink cartridge (black) ERC-27B	\$12.75
23112	Power supply	\$132.00
34344	Additional operating manual	\$21.00
72309	Power supply, 12 VDC vehicle cigarette plug	\$290.00
Cables		
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	\$70.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
41279	25-pin D-sub male to 9-pin D-sub male, RS-232 with handshaking	\$70.00
32810	25-pin D-sub male to 8-pin D-sub male, RS-232 with handshaking	\$69.00
Consult*	Custom 20 mA/RS-232 serial interface cable	\$100.00

*Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.

Standard cable length is 5ft. \$2.00 charge for each additional foot.

Standard Features

- High-speed printing
- Single copy or up to four-part multicopy ticket printing
- RS-232 serial communication

Note: Does not support double-strike commands.

Specifications

Print Speed:

1.9 to 2.3 lines per second (5 × 7 character, 3 dot line spacing)

Column Capacity:

35/42 columns

Characters Per Line:

35 standard font

Form Thickness:

Single-ply: 0.003 to 0.009 in (0.08 to 0.23 mm)
Copy paper: 0.003 to 0.014 in (0.08 to 0.36 mm)

Ribbon:

Cassette-type purple ribbon
Ribbon life is approximately 1.5 million characters (continuous prints)
Black ink also available

Serial Interfaces:

RS-232 (DB-25F) compatible

Baud Rates:

1200, 2400, 4800, 9600, selectable

Parity:

7 or 8 bits, none, even or odd

Dimensions:

(L × W × H)
7.49 × 7.08 × 3.99 in
(190.5 × 180 × 101.5 mm)

Warranty:

One-year limited
(includes printhead)

Approvals:

CE Listed
UL Listed
CSA



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
68502	TM-U590 ticket printer, 115/230 VAC power supply, cool white	12lb	\$1,265.00
128726	TM-U590 ticket printer, 115/230 VAC EU power supply, cool white	12lb	\$1,309.00
164391	TM-U590, 115/230 VAC power supply, cool white	12lb	\$1,452.00

Options/Accessories

Part #	Description	Price
68525	Ink cartridge (purple) ERC-31	\$16.00
104145	Ink cartridge (black) ERC-31B	\$16.00
23112	Power supply, U.S. version PS-180	\$132.00
128746	Power supply, European version of PS-180	\$145.00
111840	Protective dust cover	\$69.00
68562	Additional operating manual	\$14.00
68725	Technical manual	\$41.00
72309	Power supply, 12VDC vehicle cigarette plug	\$290.00
Cables		
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	\$70.00
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
41279	25-pin D-sub male to nine-pin D-sub male, RS-232 with handshaking Interfaces to Rice Lake indicators with a serial port screw terminal connection	\$70.00
32810	25-pin D-sub male to eight-pin D-sub male, RS-232 with handshaking Interfaces with DC-190, DC-100, DC-200, DC-300	\$69.00
Consult	Custom 20mA/RS-232 serial interface cable	\$100.00

Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type.

Standard cable length is 5ft. \$2.00 charge for each additional foot.

Standard Features

- High-speed printing
- Single copy and up to five-part
- Wide slip capability of A4 size documents
- Remote-printing functionality sent via RS-232
- Supports double-strike commands

Specifications

Print Speed:

2.8 lines per second printing for 88 columns of print
4.9 lines per second printing for 40 columns of print

Print Width:

5.2 in

Paper Dimensions:

(L × W)
2.76 × 2.76 in/11.69 × 8.26 in
(70 × 70 mm/297 × 210 mm)

Paper Thickness:

0.003 to 0.014 in (0.09 to 0.36 mm)

Interfaces:

Serial: Bidirectional parallel, RS-232 (DB-25F)/ RS-485
USB

Power:

24 VDC ± 10%

Ribbon:

ERC-31 (purple)

Dimensions:

(L × W × H)
10.47 × 9.92 × 7.28 in
(266 × 252 × 185 mm)

Warranty:

One-year limited (includes printhead)

Approvals:

CE Listed
FCC
cULus Listed

Star® SP742

Dot Matrix Printers



Approvals



Part Number/Price

Part #	Description	Est. Weight	Price
103142	SP742 RS-232 tape printer, cutter	9 lb	\$572.00

Consult factory for models with a parallel interface.

Options/Accessories

Part #	Description	Price
69921	Ink ribbon (purple) SP500, SP2000, SP200, series	\$12.75
103728	Ink ribbon (black), SP700 Series	\$12.75
69916	One-ply paper roll, (W × D) 3 × 3 in, 150 ft roll, Bond, 3 in OD	\$5.25
69915	Two-ply paper roll, (W × D) 3 × 3 in white/canary yellow, 90 ft roll, 3 in OD	\$7.50
121331	Wall mount bracket, SP700 Series	\$31.50
Cables		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	\$70.00
72440	25-pin to nine-pin D-sub female cable	\$67.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00

Standard Features

- Spill-proof cover
- Single-color highlights
- Power switch cover
- Internal universal power supply
- Serial interface
- Star and ESC/POS emulation
- Black mark sensor
- More than four lines per second print speed
- Auto cutter and tear bar versions
- Prints multiple copies (original and two copies)
- High reliability
- Prints graphics

Specifications

Print Speed:

13 RPM

Paper Width:

70 and 58 mm (with paper guide)

Power:

110 to 230 VAC

Connectivity:

Nine-pin serial (DB-25F), parallel, USB, Ethernet, Wi-Fi

Dimensions:

(L × W × H)
245 × 152 × 160 mm

Warranty:

Three-year limited

Approvals:

cULus Listed

PRINTERS

Star® TSP 847

Receipt Thermal Printer



Standard Features

- Direct thermal
- Small desktop footprint
- Jam-proof patented cutter with full or partial cut
- Wide area printing
- Zoom raster drive allows letter-sized documents to be printed in 4.4 format
- Logo storage capability

Specifications

Print Speed:

1,200 dots per second (150 mm/sec)

Paper Width:

Max 104 mm

Resolution:

203 dpi

Bar Codes:

Code 39, Interleaved 2 of 5, JAN/EAN/UPC, Code 128, Code 93, Coderbar, GS1-128

Roll Paper:

Paper width: 111.5 mm (4.4 in)
Thickness: 65 to 150 mm
Diameter: 4 in

Interface:

RS-232 serial (DB-25F)

Temperature:

Operating:
41 °F to 113 °F (5 °C to 45 °C)

Dimensions:

(W × D × H)
7 × 8.4 × 5.8 in
(180 × 213 × 148 mm)

Warranty:

Three-year limited

Part Number/Price

Part #	Description	Est. Weight	Price
107617	TSP847D-24 line receipt printer (requires power supply)	5 lb	\$798.00

Options/Accessories

Part #	Description	Price
69903	Power supply, PS-60-24A	\$105.00
72309	Power supply, 12 VDC with car adapter	\$290.00
107618	Thermal paper 4.4 in wide, 4 in OD	\$22.00
Cables		
15547	Blunt-end 25-pin D-sub male RS-232	\$70.00
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
72440	25-pin male to nine-pin female	\$67.00

PRINTERS

Star® TSP743 II

Direct Thermal Printer



Approvals



Standard Features

- Two-color printing (software enabled)
- Small footprint
- Easy load "drop-in and print" paper loading
- Adjustable paper width
- Logo storage utility for easy logo data
- Drawer kickout device function
- Cutter
- Easy to change "cartridge-type interface" from RS-232 (DB-25F) to parallel

Part Number/Price

Part #	Description	Est. Weight	Price
69907	*TSP743 II, RS-232 with power supply, 115/230 VAC	8 lb	\$693.00
69908	*TSP743 II, RS-232 only, 24 VDC	8 lb	\$693.00
85929	*TSP743 II, parallel without power supply	8 lb	\$693.00

* If using for labels with black mark, request printer to be configured by Rice Lake Weighing Systems

Options/Accessories

Part #	Description	Price
TSP654		
69903	Power supply, PS-60-24A	\$105.00
69917	One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 in core 230 ft	\$6.00
107041	MaxStick receipt paper for TSP654 3 1/8 in wide 150 ft long adhesive strip	\$18.75
72309	Power supply, 12 VDC with vehicle cigarette lighter	\$290.00
71355	Parallel cartridge option	\$63.00
TSP743		
69919	Wall mount bracket	\$84.00
70598	Label, DTL, (W × L × D) 3 × 1 × 4 in, with black line timing mark 1,600 labels/roll	\$29.00
70597	Label, DTL, (W × L × D) 3 × 2 × 4 in, with black line timing mark 900 labels/roll	\$29.00
Cables		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable (Rice Lake indicators)	\$70.00
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable	\$70.00
72440	25-pin to nine-pin D-sub female cable	\$67.00

Specifications

Print Speed:

7 in (177.8 mm) per second,
60 lines per second at 3 mm per line
(180 mm/sec)

Print Width:

2.83 in (80 mm)
Optional: 2.05 in (52 mm),
3.15 in (80 mm)

Resolution:

203 dpi (8 dots/mm)

Bar Codes:

UPC-A/E, JAN/EAN-8/13, Code 39/93/128,
Codabar (NW7)

Paper Width:

Adjustable 3.15 in (80 mm)
Optional: 3.25 in (82.5 mm)

Paper Thickness:

0.003 to 0.006 in (0.065 to 0.150 mm)

Roll Diameter:

3.5 in (90 mm)

Paper Roll Core:

0.50 to 1.00 in (12 to 25.4 mm)

Printer Reliability:

60 million lines MCBF (CRT)

Interface:

RS-232 serial DB-25F

Temperature:

Operating:
41 °F to 113 °F (5 °C to 45 °C)

Dimensions:

(W × H × D)
5.79 × 5.83 × 8.39 in
(147 × 148 × 213 mm)

Warranty:

Parts: Three-year limited
Printhead: One-year limited

Approvals:

FCC
cULus Listed



Standard Features

- Open ACCESS™ design for easy media loading
- Fully enclosed 5.0 in (127 mm) media compartment
- Double-walled ABS case construction
- EPL and ZPL® programming language, co-resident
- 32-bit RISC processor
- 8 MB SDRAM, 4 MB flash memory
- Zebra E3 print head energy control
- Auto-calibration of media
- Five resident expandable EPL2® fonts
- Auto-switching 100 V and 240 V power supply
- Linear and 2-D bar code symbologies
- Transmissive and reflective media sensing
- Head-up sensor
- Tear-off mode
- Certified Microsoft® Windows® drivers

Part Number/Price

Part #	Description	Est. Weight	Price
216767	ZD411, direct thermal, USB/Ethernet/Bluetooth, 120 VAC U.S. power cord	3 lb	\$500.00
219364	ZD411, thermal transfer, USB, Ethernet, BT, US 120 VAC	3 lb	\$645.00

Parallel and Ethernet models available by special request

Options/Accessories

Part #	Description	Price
212815	RS-232 option card, compatible with ZD411 and ZD421 (field installable)	\$32.00
38941	Cleaning pens for open printhead printers, 12/box	\$67.00

Label Stock/Ribbon

110346	Direct thermal, (W × L × D) 1.2 × .85 × 5 in with perf., 2,700/LPR	\$17.00/roll
110347	Direct thermal, (W × L × D) 2.25 × 1.25 × 5 in with perf., 2,100/LPR	\$17.00/roll
40332	Direct thermal, (W × L × D) 2.25 × 2 × 5 in with perf., 1,445/LPR	\$19.00/roll
110348	Direct thermal, (W × L × D) 2.25 × 3 × 5 in with perf., 950/LPR	\$18.00/roll
110349	Direct thermal, (W × L × D) 2.25 × 4 × 5 in with perf., 700/LPR	\$17.00/roll
65617	Direct thermal, (W × L × D) 2.25 × 4.5 × 5 in with perf., 600/LPR	\$19.00/roll
126092	Thermal paper, (W × D) 2 × 5 in, 6 rolls/case	\$96.00/case
207358	Ribbon, wax/general purpose, 2.5 in × 243 ft, 0.5 in core	\$9.00

Cables

41276	Serial cable, 6 ft (DB9 male to blunt end) (Rice Lake indicators)	\$77.00
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
64794	DB9 RS-232 cable DB9F to DB9M	\$69.00

Specifications

Resolution:

203 dpi (8 dpmm)

Print Length:

0.005 to 39.0 in (0.125 to 991 mm)

Print Speed:

2 to 4 in per second (ips)

Media:

Width: 1.00 to 2.36 in (25 to 60 mm)

Interface:

USB, Ethernet, and Bluetooth (Serial Optional)

Label Length:

Minimum: 0.38 in (9.7 mm)

1.0 in with optional cutter

Maximum 39 in (991 mm)

Inner Core: 1.0 in

Max roll diameter: 5 in

Sensing: gap, black line, notch

Type: roll-fed, fan fold, die cut or continuous with or without black mark, tag stock

Bar Codes:

Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, EAN-8, EAN-13, EAN-14, UPC-A and UPC-E with EAN 2 or 5 digit extensions, Plessey, POSTNET, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, MSI, Codabar, and GS1 DataBar (formerly RSS), PDF417, MicroPDF417, Code 49, Maxicode, Codablock, Data Matrix, QR code, Aztec

Power:

100 to 240 VAC, 50/60 Hz, US power cord

Temperature:

Operating:

-40 °F to 105 °F (-40 °C to 40.5 °C)

Dimensions:

8.5 × 4.5 × 6.0 in

(220 × 115 × 151 mm)

Warranty:

One-year limited

Zebra® ZD421

Direct Thermal/Thermal Transfer Label Printer



Standard Features

- Auto sense EPLZ or ZPL
- Tear bar

Options

- RS-232 (DB-9F)
- Peeler mechanism
- Models available with Ethernet

Specifications

Print Speed:

6 ips

Print Width:

4.09 in (104 mm)

Paper Width:

0.75 to 4.25 in (19 × 108 mm)

Paper Thickness:

0.003 to 0.0075 in (0.08 × 0.19 mm)

Paper Diameter:

5 in (127 mm)

Paper Roll Shaft:

0.5 and 1.0 in (13 × 25 mm) standard

Resolution:

203 dpi/8 dots per mm

Memory:

512 MB flash, 128 MB SDRAM

Ribbon Outside Diameter:

2.6 in

Ribbon Standard Length:

984 ft (300 m)

Ribbon Ratio:

1:4 media to ribbon

Ribbon Width:

0.585 to 4.65 in

Ribbon Core Inner Diameter:

1 in

Interface:

USB 2.0 host
Ethernet TCP/IP
Optional: RS-232 serial (DB-9F)

Temperature:

Operating: 40 °F to 105 °F
(4 °C to 41 °C)
Storage: -40 °F to 140 °F
(-40 °C to 60 °C)

Dimensions:

(L × W × H)
ZD421: 8.69 × 6.98 × 5.93 in
ZD421T: 10.5 × 8.0 × 7.5 in

Warranty:

One-year limited

Part Number/Price

Part #	Description	Est. Weight	Price
Direct Thermal			
212409	ZD421d direct thermal printer, USB host	10 lb	\$847.00
212410	ZD421d direct thermal printer, USB host, Ethernet LAN	10 lb	\$1,067.00
Thermal Transfer			
212406	ZD421t thermal transfer printer, USB host	10 lb	\$902.00
212411	ZD421t thermal transfer printer, USB host, Ethernet LAN	10 lb	\$1,210.00

Options/Accessories

Part #	Description	Price
213390	Peeler option, ZD421t, front mount, field installable	\$44.00
213356	Peeler option, ZD421d, front mount, field installable	\$44.00
212815	RS-232 option, ZD421 field installable	\$32.00
41276	Interface cable DB9 to blunt	\$77.00
Label Stock/Ribbon		
192736	Ribbon core option (ZD421t) to accept 1 in ribbon cores (set of 2)	\$29.00
192724	2000 wax ribbon (ZD421t) 2.52 in × 984 ft, 1 in core	\$5.00
192725	2000 wax ribbon (ZD421t) 3.31 in × 984 ft, 1 in core	\$7.00
192726	2000 wax ribbon (ZD421t) 4.23 in × 984 ft, 1 in core	\$9.00
192727	5555 wax/resin ribbon (ZD421t) 2.52 in × 984 ft, 1 in core	\$14.00
192728	5555 wax/resin ribbon (ZD421t) 3.31 in × 984 ft, 1 in core	\$18.00
192729	5555 wax/resin ribbon (ZD421t) 4.33 in × 984 ft, 1 in core	\$24.00
192730	5095 resin ribbon (ZD421t) 2.52 in × 984 ft, 1 in core	\$29.00
192731	5095 resin ribbon (ZD421t) 3.31 in × 984 ft, 1 in core	\$38.00
192732	5095 resin ribbon (ZD421t) 4.33 in × 984 ft, 1 in core	\$50.00
207358	Ribbon, thermal transfer, 2.25 in, 243 ft, wax, 1/2 in core	\$9.00

PRINTERS



Approvals



Standard Features

- Apple iOS, Android and Windows Mobile connectivity
- Direct thermal printing of bar codes, text and graphics
- CPCL, EPL™ and ZPL® programming languages
- Belt clip for unobtrusive and convenient printing
- Black mark using fixed center-position sensors
- Easy-to-use peel and present mode
- Label present sensor for issuing labels one at a time
- Tear bar for easy dispensing
- Center-loading media locking for variable roll widths
- Large, easy-to-read LCD control panel
- Color display can be customized
- Tolerance of multiple drops from 6 ft/1.8 m to concrete
- 400 MHz 32-bit ARM processor
- XML support
- Supports vertical and horizontal printing
- Printers can be used in any orientation
- QR bar code links to web-based help pages
- Label odometer
- NTP (Network Time Protocol) support via Wi-Fi or Ethernet

Part Number/Price

Part #	Description	Est. Weight	Price
204373	ZQ630 kit, 4 in direct thermal printer, 203 dpi, USB/Wi-Fi/Bluetooth® (Kit includes AC adapter, and USB cable)	3 lb	\$1,557.00
204370	ZQ630 printer, 4 in direct thermal printer, 203 dpi, USB/Wi-Fi/Bluetooth® (AC adapter and USB cable sold separately)	3 lb	\$1,436.00

Options/Accessories

Part #	Description	Price
181233	Power supply, 12-24 VDC	\$65.00
181236	Power supply, 15-60 VDC	\$110.00
181234	RAM Handi-Mount kit	\$365.00
188144	AC adapter	\$110.00
188145	Receipt paper	\$15.00
Label Stock/Ribbon		
181238	4 in × 4 in direct thermal labels, with Gap. 36 rolls per case	\$473.00
181239	4 in × 2 in direct thermal labels, with Gap. 36 rolls per case	\$473.00
Cables		
204372	USB cable, USB 2.0 A to MINIB	\$24.00
41276	Serial cable, 6 ft (DB9 male to blunt end) (Rice Lake indicators)	\$77.00

Specifications

Power:

PowerPrecision+ 6800 mAh Li-Ion rechargeable battery
Built-in battery charger

Paper:

Width: 4.40 in
Thickness: 2.3 to 5.5 mil tag stock or 6.5 mil label stock

Diameter:

2.6 in

Paper Roll Shaft:

0.75 in

Resolution:

203 dpi

Memory:

256 MB RAM/512 MB Flash

Bar Codes:

Codabar (NW-7), Code 39, Code 93, Code 128, EAN-8, EAN-13, UCC/EAN 128, UPC-A, UPC-E, PDF417, Micro PDF417, QR Code, TLC39

Print:

Length: 32 in

Speed:

4.5 ips

Interface:

USB, RS-232, Wi-Fi, Bluetooth®

Rating:

IP43 dust- and water-resistance rating (IP54 with soft case)

Temperature:

Operating:
-4 °F to 122 °F (-20 °C to 50 °C)

Warranty:

One-year

Approvals:

CE
TUV
CSA



Standard Features

- Requires a 633 nm visible light diode (VLD) scanning device for bar codes
- All-temperature permanent acrylic adhesive with short repositioning time, withstands some contact with alcohol, blood, grease and water

Applications

- Recommended for paper, corrugated containers, folding cartons with exterior varnish, glass, metal, PVC, polyesters, acetate, cellophane XT polymer, polystyrene, and some treated polypropylenes and polyethylenes

Not recommended for applications with exposure to sunlight, fluorescent lamps or heat

Part Number/Price

Part #	Width × Length	Roll Dia.	Case Qty	Labels Per Roll	Perf.	Price
0.75 in Core Size						
110463	2.00 × 3.00 in	2 in	36	125	Yes	\$104.00/case
1 in Core Size						
110346	1.20 × 0.85 in	5 in	6	2,710	Yes	\$17.00/roll
110350	2.00 × 1.00 in	5 in	16	2,600	Yes	\$20.00/roll
37354	2.25 × 1.25 in	2 in	12	260	Yes	\$9.00/roll
40332	2.25 × 2.00 in	5 in	12	1,445	Yes	\$19.00/roll
110348	2.25 × 3.00 in	5 in	16	950	Yes	\$18.00/roll
37352	2.25 × 4.00 in	4 in	12	380	Yes	\$11.00/roll
110349	2.25 × 4.00 in	5 in	12	700	Yes	\$17.00/roll
65617	2.25 × 4.50 in	5 in	16	600	Yes	\$19.00/roll
110347	2.25 × 1.25 in	5 in	16	2,100	Yes	\$17.00/roll
156746	3.00 × 2.00 in	4 in	8	800	Yes	\$22.00/roll
110352	3.00 × 3.00 in	5 in	8	950	Yes	\$25.00/roll
110351	3.50 × 1.00 in	5 in	8	2,600	Yes	\$29.00/roll
110353	4.00 × 1.00 in	5 in	8	2,500	Yes	\$29.00/roll
37350	4.00 × 1.50 in	4 in	12	960	Yes	\$36.00/roll
110354	4.00 × 1.50 in	5 in	8	1,800	Yes	\$28.00/roll
110345	4.00 × 2.00 in	5 in	8	1,400	Yes	\$28.00/roll
110355	4.00 × 2.50 in	5 in	8	1,100	Yes	\$29.00/roll
53251	4.00 × 3.00 in	5 in	12	930	Yes	\$35.00/roll
37348	4.00 × 3.00 in	2 in	12	110	Yes	\$8.00/roll
40331	4.00 × 4.00 in	5 in	8	745	Yes	\$37.00/roll
110356	4.00 × 5.00 in	5 in	8	500	Yes	\$28.00/roll
37345	4.00 × 6.00 in	5 in	8	450	Yes	\$26.00/roll
3 in Core Size						
21776	3.00 × 3.00 in	8 in	8	2,000	Yes	\$77.00/roll
156745	3.00 × 5.00 in	8 in	8	1,200	Yes	\$37.00/roll
91303	4.00 × 2.00 in	8 in	4	2,900	Yes	\$83.00/roll
43937	4.00 × 4.00 in	8 in	4	1,500	Yes	\$50.00/roll
25935	4.00 × 6.00 in	8 in	4	1,000	*	\$45.00/roll
150921	4.00 × 6.00 in	8 in	4	1,000	Yes	\$40.00/roll
25975	4.25 × 2.50 in	6 in	6	1,090	Yes	\$34.00/roll
20531	4.50 × 2.50 in	8 in	4	2,500	*	\$67.00/roll
Star Labels (1 in Core Size)						
70598	Black line, 3 × 1 in	4 in	10	1,600	No	\$29.00/roll
70597	Black line, 3 × 2 in	4 in	10	900	No	\$29.00/roll
Medical						
107134	1 × 11 in Datamax O-Neil Safed-Band, wristband	5 in	4	350		\$525.00/case

*Perforated liner available upon request at no charge. Minimum order quantities may apply.

NOTE: 8 and 10 in diameter rolls are not Allegro compatible

Custom label quote form online at www.ricelake.com/customlabel



DTL-Plus



DTT

Standard Features

DTL Plus/DTT

- Top-coated white matte finish
- Requires a visible light (633 nm) scanning device for bar codes
- Withstands some contact with alcohol, blood, grease and water
- Not recommended for applications with exposure to sunlight, fluorescent lamps or heat

Part Number/Price

Part #	Description	Price
109340	3 in wide continuous tag stock, 7.2 mil, 3 in core, 8 in O.D., 480 ft wound out	\$50.00
109298	4 in wide continuous tag stock, 7.2 mil, 3 in core, 8 in O.D., 480 ft wound out	\$56.00
119829	5 in wide perforated, two up, fan folded stacks of 1,000	\$1.00 each

DTL-SYN

Direct Thermal Label



Standard Features

DTL-SYN Synthetic label


- Top-coated white matte finish
- Requires a visible light (633 nm) scanning device for bar codes
- All-temperature permanent acrylic adhesive with short repositioning time
- Withstands some contact with alcohol, blood, grease and water

Part Number/Price

Part #	Description	Price
109448	3.25 x 3.25 in, 3 in core, 8 in O.D., 1,800 LPR, wound out, 208 roll minimum order	\$119.00/roll

TTL

Thermal Transfer Label



Standard Features

- All-temperature permanent acrylic adhesive
- Withstands some contact with alcohol, oil, grease, blood and water

Part Number/Price

Part #	Width × Length	Roll Dia.	Case Qty	Labels Per Roll	Perf.	Price
1 in Core Size						
110357	1.50 × 1.00 in	5 in	8	2,260	Yes	\$15.00/roll
110362	2.00 × 1.00 in	5 in	8	2,260	Yes	\$22.00/roll
110358	2.25 × .750 in	5 in	6	3,320	Yes	\$20.00/roll
110360	2.25 × 3.00 in	5 in	6	930	Yes	\$21.00/roll
110359	2.25 × 1.25 in	5 in	12	2,100	Yes	\$17.00/roll
110365	4.00 × 2.00 in	5 in	6	1,370	Yes	\$29.00/roll
53261	4.00 × 3.00 in	5 in	12	930	Yes	\$32.00/roll
110366	4.00 × 4.00 in	5 in	12	700	Yes	\$24.00/roll
110367	4.00 × 6.00 in	5 in	12	475	Yes	\$34.00/roll
3 in Core Size						
21785	2.00 × 1.00 in	8 in	12	5,500	*	\$15.55/roll
25945	2.00 × 1.00 in	6 in	12	2,550	*	\$9.00/roll
66541	2.50 × 1.75 in	8 in	2	3,600		\$106.00/roll
44347	2.50 × 1.50 in	8 in	8	3,600	No	\$160.00/case
20671	3.00 × 3.00 in	8 in	8	2,000	*	\$41.00/roll
48408	3.50 × 1.00 in	8 in	4	5,500	Yes	\$130.50/case
156741	4.00 × 4.00 in	8 in	4	1,500	Yes	\$33.00/roll
21788	4.00 × 6.00 in	8 in	4	1,000	*	\$24.00/roll
20573	4.00 × 6.50 in	8 in	4	900	*	\$25.00/roll
156742	4.00 × 6.00 in	8 in	4	1,000	Yes	\$24.00/roll
20536	4.50 × 2.50 in	8 in	4	2,500	*	\$41.50/roll
Kit, 4 label rolls, 2 ribbons, 1 cleaning card						
126629	4.00 × 4.00 in	8 in	1	1,500		\$187.00/case

*Perforated liner available upon request at no charge. Minimum order quantities may apply.

NOTE: 8 in diameter rolls are not Allegro compatible. Custom label quote form available online at www.ricelake.com/customlabel

NOTE: Not recommended for long-term exposure to water or other liquids

PRINTERS

Fantastock

Thermal Transfer Label

Part Number/Price

Part #	Width × Length	Roll Qty.	Case	Labels Per Roll	Price
1 in Core Size					
35417	Fantastock 4 × 2.88 in	4	8	500	\$37.50/roll
126114	3 × 1 in TTL Fantastock	4	8	500	\$53.00/roll
129377	4 × 2.5 in	5	8	1,650	\$169.00/roll

NOTE: 8 in diameter rolls are not Allegro compatible

Standard Features

- Withstands some contact with alcohol, oil, grease, blood and water
- Suited for alphanumeric bar codes and graphics
- Top-coated white matte finish



Standard Features

- Withstands some contact with alcohol, oil, grease, blood and water
- Suited for alphanumerics, bar codes and graphics
- Top-coated white matte finish

Part Number/Price

Part #	Width × Length	Labels Per Roll/ft.	Perf.	Price
3 in Core Size				
89190	4 in wide continuous 7.5 pt	4,000 ft	No	\$51.00/roll
107621	3.25 in wide × continuous 7.5 pt, 11 in O.D., 50 roll minimum order	1,010 ft	No	\$83.00/roll
124757	4.5 × 2.5 in, with sensing notch 20 roll minimum order	2,300 ft	Yes	\$51.50/roll

NOTE: Not recommended for long-term exposure to water or other liquids

SDR Super Durable Ribbon



Standard Features

- 4.6 micron, thermal transfer resin-based ribbon
- Smudge and smear proof
- 1,182 ft (360.3 m) long (one ribbon prints two rolls of 8 in (203 mm), OD label or tag stock)
- Avoid exposure to heat, humidity and sunlight during storage

Part Number/Price

Part #	Width × Length	Color	Case Qty	Datamax Comp	Zebra/Elton Desktop Comp	Zebra Ind. Comp.	Price
1/2 in Core Size Not for all 2 in wide printers							
37366	2.50 in × 242 ft	No	12	No	800009-002	No	\$6.85/roll
126115	3.27 in × 243 ft	No	36	221967	No	No	\$11.00/roll
37368	4.30 in × 242 ft	No	12	No	800009-004	No	\$12.00/roll
92633	4.33 in × 360 ft	No	24	226757	No	No	\$20.00/roll
1 in Core Size							
21772	4.00 in × 1182 ft	Yes	24	221716	No	No	\$1,015.00/case
52343	4.30 in × 1476 ft	No	6	No	5095BK11045	Yes	\$89.00/roll
129378	4.30 in × 984 ft	—	24	296639	—	—	\$48.00/roll

Scannable colors include: Blue, Red, White, Gold

MaxWax™ GPR

General-Purpose Ribbon



Standard Features

- 4.6 micron thermal transfer wax/resin ribbon
- Smudge and scratch resistant
- 1,182 ft (360.3 m) long (one ribbon prints two rolls of 8 in (203.2 mm) OD label or tag stock)
- Avoid exposure to heat, humidity and sunlight during storage

Part Number/Price

Part #	Width × Length	Color	GoDex Comp.	Datamax Comp.	Zebra/Eltron Comp.	Zebra Industrial Comp.	Case Qty	Price
1/2 in Core Size Not for all 2 inch wide printers								
81212*	2.50 in × 244 ft	No		Z28GPRM064074	8000130-002	No	12	\$9.00/roll
37362	2.50 in × 298 ft	No		226351	800008-002	No	36	\$8.00/roll
35477	3.50 in × 360 ft	No		226455	No	Yes	12	\$10.00/roll
37364	4.30 in × 298 ft	No		226357	800008-004	No	36	\$14.00/roll
75895*	4.30 in × 244 ft	No		Z28GPRM110074	800130-104	No	12	\$20.00/roll
35478	4.33 in × 360 ft	No		226457	No	Yes	12	\$14.00/roll
53265	1.30 in × 298 ft	No		No	800008-001	No	36	\$3.15/roll
1 in Core Size								
178965	4.30 in × 984 ft	No	GR4010				6	\$33.00/roll
110537	2.50 in × 984 ft	No			ZEBGPRM064300		24	\$11.00/roll
34054	3.00 in × 1181 ft	Yes		226102	No	No	6	\$17.25/roll
40787	4.30 in × 1189 ft	No		No	800010-004	Yes	6	\$37.00/roll
110536	4.30 in × 984 ft	No		296143	NO	No	24	\$16.25/roll
34058	4.50 in × 1182 ft	Yes		226100	No	No	6	\$27.50/roll
42474	6.00 in × 1476 ft	Yes		224108	No	No	24	\$42.90/roll
GPR Plus (for use with Kimdura Stock)								
53611**	1.57 in × 1476 ft	No		No	No	5095BK04045	6	\$37.00/roll
20538	2.0 in × 1182 ft	No		222103	No	No	36	\$8.40/roll
20539	3.00 in × 1182 ft	No		222102	No	No	6	\$105.25/case
34056	4.00 in × 1182 ft	No		222116	No	No	24	\$34.00/roll

Prices for black ribbon only.

Color ribbon—contact RLWS sales for prices and availability.

Scannable colors include: Silver, gold, green, blue, brown, purple, maroon, midnight blue, fuchsia, kelly green, royal blue, lavender


Additional colors available: Red, orange, yellow, white, pink, pumpkin

* Ribbon for TLP2844

** Resin Performance

PRINTERS

Tape and Ticket Printer Impact Ribbons



Standard Features

TicketPress:

- Cartridge-type
- Ribbon life approximately 3 million characters

SP2200 and SP2000:

- Cartridge-type
- Ribbon life is approximately 1 million standard characters

IDS-150A, IDS-152, and IDS-160:

- Inked spools

TM-U295, TM-U200, TM-300:

- Cassette-type
- TM-U295: Ribbon life is approx. 1.5 million standard characters
- TM-U200 and TM-300: Ribbon life is approx. 4 million characters (continuous printing)

Citizen® CBM-750 and Citizen® iDP-3111:

- Cassette-type
- CBM-750: Ribbon life is approx. 4 million lines (continuous printing) iDP-3111: Ribbon life is approx. 1 million lines (continuous printing)

Okidata 184 Turbo and 320:

- Self-inking
- Ribbon life is approximately 3 million characters

Part Number/Price

Part #	Description	Price
Line Printer		
20664	Okidata 184 Turbo and 320 ribbon cartridge	\$8.50
Tape Printer		
41902	Citizen CBM-750 red/black ribbon cartridge	\$10.50
31296	Epson TM-U200/TM-U220 and TM-300 purple ink cartridge (ERC 30, 34)	\$12.75
66499	Epson TM-U200/TM-U220 and TM-300 red/black ink cartridge	\$12.75
20447	IDS-160/Star® DP8340 purple ribbon cartridge	\$10.50
103728	Star SP700 black ribbon cartridge	\$12.75
Tape Kiosk Printer		
69920	Star SP349 and SP312 Purple ribbon cartridge	\$13.75
Ticket Printer		
29583	Epson® TM-U295 black ink cartridge	\$12.75
29584	Epson TM-U295 purple ink cartridge (ERC 27)	\$12.75
68525	Epson TM-U590 purple ink cartridge (ERC-31)	\$16.00
20440	IDS-150A and IDS-152 purple ink ribbon	\$26.50
20308	SP2200 and SP2000 black ink cartridge	\$25.50
69921	Star SP298, SP2320 and SP2520 purple ribbon cartridge	\$12.75
128031	TicketPress™ black ribbon cartridge	\$28.00

Don't see a ribbon or paper roll you need? Send us the manufacturer name and model of the printer and we will provide you a quotation.

Tape Printer Paper Supplies



Standard Features

IDS-150A, IDS-152, IDS-160, TM-U200, TM-300, and Citizen® CBM-750:

- One-ply paper roll (W × L): 3 × 150 ft (76.2 × 45.7 m)
- Two-ply paper roll (W × L): 3 × 90 ft (76.2 × 27.4 m)

Citizen® iDP-3111:

- One-ply paper roll (W): 2.25 in (57.1 mm)

Star®:

- One- and two-ply paper roll (W × L): 3 in × 3 ft (76.2 × 0.9 m)
- One-ply thermal paper roll (W × L): 3.125 in × 3.25 ft (76.2 × 0.99 m), 8 in roll diameter

Part Number/Price

Part #	Description	Price
IDS-150A, IDS-152, IDS-160, TM-U220, TM-300, and Citizen CBM-750		
69916	One-ply bond, (W × L) 3 in × 150 ft (76.2 mm × 45.7 m), 3 in dia., 1/2 in core	\$5.25/roll
69915	Two-ply bond, (W × L) 3 in × 90 ft (76.2 mm × 27.4 m), 3 in dia, 1/2 in core white/canary yellow	\$7.50/roll
Citizen iDP-3111		
42870	One-ply bond, (W × L) 2.25 in × 150 ft (57.1 mm), 7/16 in core 2 7/8 in outer diameter	\$7.00/roll
Star		
69916	One-ply bond, (W × L) 3 in × 150 ft (76.2 mm × 45.7 m), 3 in dia., 1/2 in core	\$5.25/roll
69915	Two-ply bond, (W × L) 3 in × 90 ft (76.2 mm × 27.4 m), 3 in dia, 1/2 in core white/canary yellow	\$7.50/roll
69917	One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 in core 230 ft	\$6.00/roll
70083	One-ply thermal, (W) 3.23 in (82 mm, 3 in dia.), 8 in roll dia. (2,020 ft long) 1 1/2 in core	\$35.00/roll
71214	One-ply plain paper, (W) 3.25 in (82.5 mm, 3 in dia.), 50 rolls per case, 3/8 in core	\$100.00/case
105711	Two-ply plain paper, (W) 3.25 in, 50 per case, 3/8 in core 3 in outer diameter	\$198.00/case
105712	Three-ply plain paper, (W) 3 in, 50 per case, 3/8 in core, 3 in outer diameter (white, canary, pink)	\$211.00/case
102950	One-ply thermal, (W) 4.4 in, 6 in outer diameter, 1 in core, 930 ft roll	\$42.50/roll
20448	One-ply bond, (W × L) 4.5 in × 165 ft, 7/16 in core, 3 in outer diameter	\$10.00/roll
42672	Two-ply, (W × L) 4.5 in × 95 ft, 3 in outer diameter	\$9.00/roll
70683	One-ply bond, (W × D) 4.5 × 3 in, sprocket feed, 140 ft	\$13.00/roll
107618	One-ply thermal, (W) 10 mm (4.4 in, 4 in) outer diameter, 500 ft	\$22.00/roll
102957	One-ply thermal, (W) 58 mm (2.28 in, 2 3/4 in) outer diameter, 1/2 in core	\$5.00/roll
Epson		
105445	One-ply thermal, (W) 80 mm (3.1 in, 6 in) outer diameter, 710 ft/roll	\$33.00/roll
105446	One-ply thermal, (W) 80 mm (3.1 in, 8 in) outer diameter, 1,268 ft/roll	\$36.00/roll
75947	One-ply thermal, (W × L) 2.25 in × 85 ft, 1 7/8 in outer diameter, Mobilink, 1/2 in core	\$6.50/roll
126092	One-ply receipt (W × L) 2 in × 574 ft, 1 in core, 5 in O.D., 6 rolls/case	\$96.00/case
Kiosk Printers		
50426	One-ply, (W × D) 3.25 in × 6 in, 7/16 in core 950 ft	\$32.00/roll
104940	One-ply thermal, (W × D) 112 mm × 5 in, 1 in core, 625 ft	\$32.00/roll
Zebra Mobile		
105566	One-ply thermal, 2 in continuous 79 ft rolls, 2.5 in OD (36 per case)	\$87.00/case
105565	One-ply thermal, 4 in continuous 79 ft rolls, 2.5 in OD (36 per case)	\$160.00/case
Misc		
66653	One-ply thermal, (W × L) 80 mm (3.1 in × 455 ft, 5 in diameter for Swecoin, Star TUP 900)	\$30.00/roll
76076	One-ply thermal, (W) 60 mm (2 3/8 in), 100 mm) outer diameter 40 mm core, wound out	\$13.75/roll
73134	One-ply bond, (W) 1 3/4 in × 1-7/8 in outer diameter, 7/16 in core	\$3.75/roll
47341	One-ply thermal, (W × L) 64 mm × 50 m, 1 9/16 in core	\$6.00/roll
110463	(W × L) 2 × 3 in label, RW 220 or RW 420, 125 labels/roll, 2 in OD, 36 per case	\$104.00/case
165865	Thermal paper, (W × D) 4 × 5 in, 6 rolls/case	\$369.00/case
166916	Thermal paper, (W × D) 8.5 in × 565 ft, continuous, 4 rolls/case	\$413.00/case

Electronic Scale Tickets

Standard Features

Hecon® Printers, EL522 & EL516 - 20266

- Triplicate interleaved
- Size (L × W): 7.875 × 4.25 in (200 × 127 mm)
- Order quantity: 500 per package
- Carbonless

20266

DATE _____ No. _____

SELLER _____

BUYER _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

GROSS _____

TARE _____

NET _____

DRIVER ON OFF WEIGHED BY _____

FORM 510

Standard Features

SP2200, SP2000 - 20265

- Triplicate interleaved, perforated and glued on one end
- Size (W × L): 5.5 × 9 in (139.7 × 228.6 mm)
- Order quantity: 500 per package
- Carbonless

20265

Limit of Carbon Coverage

ELECTRONIC SCALE TICKET No. _____

DATE _____

SELLER _____

BUYER _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

COMMODITY _____

PRICE _____

REMARKS _____

DRIVER ON OFF _____

WEIGHER _____

Form ES-4

Standard Features

Rice Lake Scales - 71630 or 105182

- Duplicate or triplicate
- Size (W × L): 4.25 × 7 in (107 × 177.8 mm)
- Attached at 4.25 side
- Order quantity: 500 per package
- Custom (duplicate): Add company name (min. order two packs)
- Custom (triplicate): Add company name (min. order two packs)
- Carbonless

Customer Name: _____

Driver On Driver Off

Customer Signature: _____

RICE LAKE

Scale for scale's work station

RM1100

Standard Features

Blank Scale Ticket - 22263



- Triplicate
- White, canary yellow and pink
- Size (L × W): 5.50 × 4.25 in (140 × 108 mm)
- Attached at 4.25 edge
- Order quantity: 100 per package
- Custom: Add company name (min. order of 1,000)
- Carbonless

PRINTERS

Part Number/Price

Part #	Description	Price
20266	Hecon Printers, EL522 and EL516, 500/pack	\$121.00
20265	SP2200, SP2000, 500/pack	\$125.00
71630	Rice Lake ticket, two part, 500/pack	\$66.00
105182	Rice Lake ticket, three part, 500/pack white, canary yellow, pink	\$95.00
22263	Blank scale ticket, 100/pack	\$28.00 each

Replacement Printheads



Part Number/Price

Part #	Description	Price
Label Printers		
78998	Eltron/Zebra® LP/TLP-2824 (2 in)	\$175.00
78999	Eltron/Zebra® LP-2844 (4 in)	\$205.00
79000	Eltron/Zebra® TLP-2844 (4 in)	\$225.00
95375	Eltron/Zebra® Z4000, S4M (203 dpi)	\$730.00
111091	Eltron/Zebra® Zebra GK, (203 dpi)	\$210.00
107532	GoDex® DT2X printhead	\$120.00
150743	GoDex® DT4xW printhead	\$205.00
150746	GoDex® G500 printhead	\$205.00
53939	Honeywell® I-4208 I-4210, I-4212 (203 dpi)	\$475.00
210807	Honeywell® M-4210, 203 dpi	\$1,287.00
96957	Honeywell® H-4212, 203 dpi	\$475.00
112517	Honeywell® E4205 (e) (203 dpi)	\$175.00
103368	Honeywell® M4206, (203 dpi)	\$990.00
118183	Honeywell® Print engine A-class model 4212, 203 dpi	\$475.00
Tape Printers		
118730	Epson® TM-U220	\$135.00
Ticket Printers		
29535	Epson® TM-290/TM-U295	\$315.00
116659	Epson® TM-U590	\$315.00
68726	Epson® TM-U590 print mechanism	\$979.00
35347	Rice Lake Weighing Systems SP2200	\$300.00
72513	Star® SP298	\$135.00

PRINTERS

Printer Cables



Part Number/Price

Part #	Description	Price
Interface Cables for TicketPress, SP-2200, TM-U295, TM-U590 and Star® Printers		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable	\$70.00
15548	25-pin D-sub male to 25-pin D-sub male 20 mA serial interface cable (SP2200 only)	\$70.00
15568	25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable (this is a kit, not a complete cable)	\$70.00
Consult	Custom 20 mA/RS-232 serial interface cable	\$95.00
Interface Cables for I-Class		
15547	Blunt end, 25-pin D-sub male RS-232 serial interface cable	\$70.00
Consult	Custom RS-232 interface cable	\$95.00
Interface Cables for Desktops, GoDEX Models, Zebra, E-4203 and M-4206		
41276	DB9 male RS-232 cable to blunt end	\$77.00
Straight Cable		
70056	DB9 male to DB9 female	\$40.00
50749	DB9 female to DB9 female	\$66.00
41279	DB25 male to DB9 male	\$70.00
72440	DB25 male to DB9 female	\$67.00
Null Modem Cable		
66535	DB9F to DB9 female, null modem	\$48.00
64794	DB9 male to DB9 female	\$69.00
USB Cable		
79074	USB-A (male) to USB-B (male) cable, 6 ft	\$35.00
156806	USB-A (male) to USB-A (male) cable, 1 m	\$35.00
156807	USB-A (male) to USB-A (male) cable, 3 m	\$50.00
156808	USB-A (male) to USB-A (male) cable, 5 m	\$60.00
156809	USB-A (male) to USB-B (male) cable, 1 m	\$55.00
156815	USB-A (male) to USB-B (male) cable, 3 m	\$55.00
156811	USB-A (male) to USB-B (male) cable, 5 m	\$70.00
Ethernet Cable/RJ45		
72697	RJ45 to RJ45, 7 ft	\$40.00
78860	RJ45 to RJ45, crossover 7 ft	\$44.00
75594	RJ45 to nine-pin female	\$70.00
156817	RJ45, 1 m	\$35.00
156818	RJ45, 3 m	\$42.00
156821	RJ45, 5 m	\$50.00
Misc. Cables and Adapters		
22436	Blunt end, nine-pin D-sub female	\$77.00
130213	Blunt end DB25 male	\$64.00
165698	Female to male gender changer	\$11.25
119064	Slimline, null modem gender changer, DB9 female/female	\$14.00
130789	Null modem DB9 M/F	\$16.00

Blunt-end cables interface to: UMC444, UMC555, UMC600, IQ700, IQ plus® 310A, IQ plus® 355, IQ plus® 390-DC, IQ plus® 510, IQ plus® 590-DC, IQ plus® 710, IQ plus® 800, and IQ plus® 810, 520 and 920i®

Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type. Standard cable length is 5ft (1.5m).



Standard Features

- Tough, flexible transparent vinyl, constructed with heavy-duty stitching
- Loose fit allows for operation of switches or controls through the dust cover
- Available for most types of scale equipment

Protect your electronic scales, weight indicators and printers with a scale veil. Reduce costly repairs and down time due to moisture penetrating through instrument enclosures during cleanup or operation.

Part Number/Price

Model	Part #	Price
Epson		
TM290/295	29582	\$58.00
TM-U200 TM-U220	35666	\$63.00
TM-U590	111840	\$69.00
Okidata		
Okidata 320/390	21226	\$65.00

Custom veils and specials available; consult factory.

PRINTERS

