## **Shackle Dimensions**

## Part Number/Price

| Part #             | W.l.l.<br>Tons                               | Size    | А       | В       | С        | D       | E        | F        | н        | L        | N       | Р        | Weight    | Price   |
|--------------------|--|---------|---------|---------|----------|---------|----------|----------|----------|----------|---------|----------|-----------|---------|
| 151357             | 3 1/4  | 0.63 in | 1.06 in | .75 in  | 2.38 in  | 0.63 in | 1.69 in  | 1.56 in  | 4.22 in  | 2.94 in  | 0.69 in | N/A      | 1.58 lb   | Consult |
| 151355             | 6 1/2  | 0.88 in | 1.44 in | 1.00 in | 3.31 in  | 0.88 in | 2.28 in  | 2.13 in  | 5.75 in  | 4.03 in  | 0.97 in | 5.00 in  | 3.95 lb   | Consult |
| 141992             | 17   | 1.50 in | 2.38 in | 1.63 in | 5.75 in  | 1.50 in | 3.88 in  | 3.63 in  | 9.88 in  | 6.88 in  | 1.62 in | 8.25 in  | 19.50 lb  | Consult |
| 151356             | 25   | 1.75 in | 2.88 in | 2.00 in | 7.00 in  | 1.75 in | 5.00 in  | 4.32 in  | 11.88 in | 8.50 in  | 2.12 in | 9.59 in  | 31.30 lb  | Consult |
| 146334             | 30   | 1.50 in | 2.38 in | 1.63 in | 5.75 in  | 1.50 in | 3.88 in  | 3.63 in  | 9.88 in  | 6.88 in  | 1.62 in | 8.25 in  | 20.80 lb  | Consult |
| 146335             | 40   | 1.75 in | 2.88 in | 2.00 in | 7.00 in  | 1.75 in | 5.00 in  | 4.32 in  | 11.88 in | 8.50 in  | 2.12 in | 9.59 in  | 33.91 lb  | Consult |
| 146336             | 55   | 2.00 in | 3.25 in | 2.25 in | 7.75 in  | 2.00 in | 5.75 in  | 5.00 in  | 13.38 in | 9.75 in  | 2.00 in | 11.00 in | 51.75 lb  | Consult |
| 151359             | 85   | 2.5 in  | 4.12 in | 2.75 in | 10.50 in | 2.72 in | 7.25 in  | 5.69 in  | 17.84 in | 12.87 in | 3.12 in | 13.58 in | 96.00 lb  | Consult |
| 151360             | 120  | 3.00 in | 5.00 in | 3.25 in | 13.00 in | 3.00 in | 7.88 in  | 6.50 in  | 21.50 in | 14.50 in | 3.63 in | 16.50 in | 178.00 lb | Consult |
| 83455              | 120  | 3 in    | 5.00 in | 3.25 in | 13.00 in | 3.11 in | 7.88 in  | 6.50 in  | 21.50 in | 14.36 in | 3.63 in | 15.13 in | 178.00 lb | Consult |
| 151361             | 175  | 4.00 in | 5.50 in | 4.25 in | 14.50 in | 4.00 in | 10.00 in | 9.00 in  | 25.69 in | 18.38 in | 4.56 in | 19.75 in | 338.00 lb | Consult |
| 151358             | 250  | 4 in    | 8.50 in | 5.00 in | 20.00 in | 4.50 in | 13.00 in | 12.00 in | 35.00 in | 24.50 in | 6.50 in | 22.68 in | 600.00 lb | Consult |
| Oversized Shackles |  |         |         |         |          |         |          |          |          |          |         |          |           |         |
| 148497             | 40   | 1.75 in | 2.88 in | 2.00 in | 10.00 in | 2.25 in | 6.00 in  | 4.32 in  | 15.35 in | 10.50 in | 2.25 in | 9.00 in  | 45.00 lb  | Consult |
| 148393             | 40   | 2.25 in | 2.88 in | 2.00 in | 12.50 in | 2.25 in | 8.00 in  | 4.32 in  | 17.85 in | 12.50 in | 2.25 in | 10.00 in | 90.00 lb  | Consult |
| 148394             | 50   | 2.00 in | 3.25 in | 2.25 in | 12.25 in | 2.50 in | 8.00 in  | 5.00 in  | 18.50 in | 13.00 in | 2.50 in | 11.00 in | 72.00 lb  | Consult |
| Shims              |  |         |         |         |          |         |          |          |          |          |         |          |           |         |
| 146534             | (For use with 50,000 ton/70,000 ton systems) |         |         |         |          |         |          |          |          |          |         |          |           | Consult |

