

# 350-10-2 single-ramp wheelchair scale

Rice Lake's 350-10-2 single-ramp wheelchair scale with handrail allows high capacity, accurate weighing for a wide range of patients. Convenient keypad tare reduces errors and increases efficiency. Foldable and lightweight, this sturdy scale is easily transported on two heavy-duty rear wheels to any location.

#### FEATURES

- Two wheels for portability
- Single ramp
- Nonslip platform
- Large 1-inch LCD display
- Motiontrap<sup>™</sup> movement compensation technology
- Unit of measure toggle or locking
- EMR capable

#### SPECIFICATIONS

**Capacity:** 1,000 × 0.2 lb (450 × 0.1 kg)

Platform Dimensions Without Ramp: (L × W × H)  $29.5 \times 32.0 \times 2.4$  in

**Power:** 9 VDC, provided by six AA alkaline batteries (included) or AC adapter (optional)

- Serial and USB data communication ports
- Bluetooth<sup>®</sup> BLE 4.0 available, part number selectable
- Tare function
- Hold function
- BMI (body mass index) function
- Factory calibrated
- Easy to store, folded depth is 11.75 in

**Battery Type:** Six AA alkaline (included)

**Battery Use:** 25 hours of continuous use with batteries Automatic power-off can be configured

**Operating Temperature:** 50 °F to 104 °F (10 °C to 40 °C)

**Display:** 5-digit LCD display, 0.75 in (1.9 mm) digit height

Approvals: c-Met, E113986

Warranty: Two-year limited



## WHEELCHAIR SCALE

| MODEL       | CAPACITY  | COMMUNICATION                  | PART#  |
|-------------|---|--------------------------------|--------|
| 350-10-2    | $1,000 \times 0.2 \text{lb} (450 \times 0.1 \text{kg})$ | USB                            | 141445 |
| 350-10-2BLE | 1,000 × 0.2 lb (450 × 0.1 kg)                           | Bluetooth <sup>®</sup> BLE 4.0 | 194739 |

# OPTIONS

| DESCRIPTION   | PART#  |
|---|--------|
| 9 VDC adapter, 120 V/230 V auto switching c-MET* Medical grade power supply | 115655 |
| 9 VDC adapter, 120 V/230 V auto switching*                                  | 133077 |
| 9 VDC adapter, 230 V**  | 102508 |
| Epson TM-U220 tape printer  | 81076  |
| Cable, RS232 scale to printer, 6 ft, 25-pin D-Sub (male) to RJ45            | 186830 |
| Cable, USB 6 ft USB-A (male) to USB-B (male)                                | 79074  |
| Cable, Communication DB9 (female) to RJ45 (male), 4 conductor               | 217091 |
|   |        |


\*NEMA 1-15 Plug [] [] \*\*CEE 7/16 Plug (0)

# SHIPPING WEIGHT

| MODEL #     | PART # | L (IN) | W (IN) | H (IN) | PACKAGE<br>WGT. (LB) | DIM WGT.<br>(LB) | SHIPPING<br>WGT. (LB) |
|-------------|--------|--------|--------|--------|----------------------|------------------|-----------------------|
| 350-10-2    | 141445 | 42     | 41     | 14     | 90                   | 174              | 174                   |
| 350-10-2BLE | 194739 | 42     | 41     | 14     | 90                   | 174              | 174                   |

#### DIMENSIONS

|   | INCHES | CENTIMETERS |   | INCHES | CENTIMETERS |
|---|--------|-------------|---|--------|-------------|
| Α | 29.5   | 74.9        | D | 9.3    | 23.5        |
| В | 32.0   | 81.3        | E | 37.5   | 95.3        |
| С | 2.4    | 6.1         | F | 45.0   | 114.3       |



An ISO 9001 Registered Company ©2024 Rice Lake Weighing Systems 03/24 Specifications subject to change without notice. Visit ricelake.com