

Part Number/Price

Part #	Description	Est. Weight	Price
68541	DeviceNet interface kit for 720i/920i indicators	3 lb	Consult

Options/Accessories

Part #	Description	Price
69949	Additional operating manual	Consult

Standard Features

- DeviceNet communication adapter
- Polled I/O connection
- 125 Kbps, 250 Kbps, and 500 Kbps baud rate
- Onboard LED diagnostics
- Floating-point commands support decimal points

Specifications

Power:

5 VDC, 270 mA

Fieldbus connector requires 24 VDC, ±10%

Communication Ports:

Twisted-pair cabling at 125, 250, or 500 Kbps Update rate is dependent on the configured baud rate and the number of network modes

Fieldbus Interface:

Pluggable screw connector

Diagnostic LEDs:

Module status and network status

Galvanic Isolation:

Bus power is separated from other electronics via DC/DC converter. The send and receive signals are isolated via opto couplers.

Dimensions:

2.13 × 3.38 × 0.59 in (86 × 54 × 15 mm)


Temperature:

Operating: 14 °F to 158 °F (-10 °C to 70 °C)

FIELDBUS CARDS

ControlNet® Interface

920i®



Part Number/Price

Part #	Description	Price		
103136	ControlNet interface for 920i indicator	Consult		
Cables				
Consult factory for coaxial cable with cord grips				

Options/Accessories

-					
	Part #	Description	Price		
	103122	Additional operating manual	Consult		

Standard Features

- Option for 920i®
- Polled I/O connection
- Onboard LED diagnostics
- Floating-point commands support decimal points

Specifications

Power:

5 VDC, 350 mA (jumper for 6 VDC)

Fieldbus Interface:

BNC connector

Diagnostic LEDs:

Module status and network status

Dimensions:

 $2.13 \times 3.38 \times 0.59$ in $(86 \times 54 \times 15 \text{ mm})$

Temperature:

Operating: 14 °F to 158 °F (-10 °C to 70 °C)