# **TOPLOADER**

# Navigator™ XT Series

# **Standard Features**

- Touchless IR (infrared) sensors minimize keypad use
- Program IR sensor to control zero, print tare, backlight and power functions
- · Backlit 0.8 in LCD display for high visibility
- Illuminated level indicator at start-up
- Integrated transportation and calibration lock switch
- Hygienic design for easy cleanup in food, laboratory and industrial applications
- Impact-resistant ABS plastic housing with polished stainless steel spill-resistant pan
- Non-skid leveling feet

# **Specifications**

# Weighing Units:

Gram, carat, ounce, pound, carat, pennyweight, troy ounce, grain, pound/ounce (see technical manual for complete listing)

## **Operating Modes:**

Weighing, percent, parts counting, checkweighing, display hold, accumulation/totalization

12 VDC 0.42 A AC adapter, 100 to 240 V, four C-batteries (not included)

# Stabilization Time:

1 second (NVT4201 = 1.5 seconds)

### **Calibration Weight:**

NVT2201: 2 lb (1 kg) NVT4201: 5 lb (2 kg) NVT6200: 10 lb (5 kg) NVT12000: 10 lb (5 kg) NVT2200: 20 lb (10 kg)

# Temperature:

10 °C to 40 °C (50 °F to 104 °F) at 20% to 85% RH

### Est. Weight:

5.1 lb (2.3 kg)

#### Warranty:

One-year limited

### Return Policy:

OHAUS standard policy - restock fee may apply

| Model    | Capacity | Readability | Linearity    | Pan Size                       | Dimensions                                | Part # | List Price |
|----------|----------|-------------|--------------|--------------------------------|---|--------|------------|
| NVT2201  | 2,200 g  | 0.1 g       | 0.1 g/±0.2 g | 9.1 × 6.9 in<br>(230 × 174 mm) | 9.5 × 9.8 × 2.9 in<br>(240 × 250 × 74 mm) | 194607 | Consult    |
| NVT4201  | 4,200 g  | 0.1 g       | 0.1 g/±0.2 g | 9.1 × 6.9 in<br>(230 × 174 mm) | 9.5 × 9.8 × 2.9 in<br>(240 × 250 × 74 mm) | 194608 | Consult    |
| NVT6200  | 6,200 g  | 1 g         | 1 g/±2 g     | 9.1 × 6.9 in<br>(230 × 174 mm) | 9.5 × 9.8 × 2.9 in<br>(240 × 250 × 74 mm) | 194609 | Consult    |
| NVT12000 | 12,000 g | 1 g         | 1 g/±2 g     | 9.1 × 6.9 in<br>(230 × 174 mm) | 9.5 × 9.8 × 2.9 in<br>(240 × 250 × 74 mm) | 194610 | Consult    |
| NVT22000 | 22,000 g | 1 g         | 1 g/±2 g     | 9.1 × 6.9 in<br>(230 × 174 mm) | 9.5 × 9.8 × 2.9 in<br>(240 × 250 × 74 mm) | 194611 | Consult    |

# **Options/Accessories**

| Part#  | Model#   | Description                            | Price   |  |  |  |  |
|--------|----------|--|---------|--|--|--|--|
| 118779 | 83032107 | RS-232 interface kit, Navigator series | Consult |  |  |  |  |
| 118780 | 83032108 | USB interface kit                      | Consult |  |  |  |  |
| 118781 | 83032109 | Ethernet interface kit                 | Consult |  |  |  |  |
| 194616 | 30467963 | Carrying case                          | Consult |  |  |  |  |
| 194615 | 30467987 | Universal AC adapter                   | Consult |  |  |  |  |

