

Picture is a representation of actual product.

Approvals








ироп reauest


Order Information

Load Rating	Part#	Est. Weight	Price
OIML C3			
10 kg	36173	2 lb	Consult
20 kg	36174	2 lb	Consult
50 kg	36175	2 lb	Consult
100 kg	36176	2 lb	Consult
200 kg	36177	2 lb	Consult
OIML D1			
5 kg	36172	2 lb	Consult

Dimensions

Rated Capacity	Н	L	L1	L2	L3	L4	L5	L6	W	W2	D
kg/mm											
5 to 200	31.0	123.0	18.0	82.0	9.9	21.0	45.0	27.9	42.0	20.1	8.2





Interchangeable Products

RICE LAKE WEIGHING SYSTEMS

RL9018SS.....page 109

RICE LAKE WEIGHING SYSTEMS

RLHBB

VPG® REVERE

SHB......page 253

METTLER TOLEDO®

MTB

Specifications

Full Scale Output:

2.0 mV/V

Output Resistance:

356 ohm

Input Resistance:

350 to 400 ohm

Material/Finish:

Stainless steel

Temperature:

Operating: 0 °F to 150 °F (-18 °C to 65 °C)

Seal Type:

Welded-seal, IP68

Safe Overload:

150% full scale **Rated Excitation:**

5 to 15 V DC

Combined Error:

0.05% full scale

Insulation Resistance:

5,000 megohm

Cable Length:

3 m

Cable Diameter:

4.8 mm PVC jacket

Cable Color Code:

Blue +Excitation Black -Excitation

White +Signal

Red –Signal Green +Sense Grey –Sense

Warranty:

One-year limited

Approvals: OIML

Ex (available upon request)