

# **Standard Features**

- Mild steel or stainless steel
- Used in the ITCM assembly
- One jam nut included with each rod end ball joint

# Part Number/Price


Part#	Safe Load*	Breaking Strength	PTFE Lined	Price			
Mild Steel							
17746	975 lb	3,915lb	YES	Consult			
17734	1,200 lb	4,916lb	NO	Consult			
17736	4,000 lb	16,238 lb	NO	Consult			
17738	7,000 lb	28,081 lb	NO	Consult			
17735	2,000 lb	8,075 lb	NO	Consult			
17737	3,250 lb	13,831 lb	NO	Consult			
17739	500 lb	2,158 lb	YES	Consult			
17740	4,000 lb	16,238 lb	YES	Consult			
17741	10,000 lb	40,572 lb	YES	Consult			
17742	10,500 lb	43,541 lb	NO	Consult			
26007	15,000 lb	76,200 lb	YES	Consult			
17747	19,000 lb	76,200 lb	YES	Consult			
17743	20,000 lb	79,728 lb	NO	Consult			
17744	24,000 lb	96,510 lb	NO	Consult			
Stainless Steel							
33505	500 lb	2,158 lb	YES	Consult			
33506	1,500 lb	7,362 lb	YES	Consult			
33507	3,000 lb	16,238 lb	YES	Consult			
33508	7,000 lb	40,572 lb	YES	Consult			
*Do not exceed the safe load							

# **Dimensions**

Part#	Α	В	С	D	E	F	Thread Size	
		ь	· ·	U	-	Г.	Tilleuu Size	
Mild Steel								
17746	1.94 in	0.37 in	1.25 in	1.00 in	2.43 in	0.50 in	3/8-24 UNF	
17734	1.94 in	0.37 in	1.25 in	1.00 in	2.43 in	0.50 in	3/8-24 UNF	
17736	2.44 in	0.50 in	1.50 in	1.31 in	3.09 in	0.62 in	1/2-20 UNF	
17738	2.87 in	0.75 in	1.75 in	1.75 in	3.75 in	0.87 in	3/4-16 UNF	
17735	2.44 in	0.50 in	1.50 in	1.31 in	3.09 in	0.62 in	1/2-20 UNF	
17737	2.87 in	0.75 in	1.75 in	1.75 in	3.75 in	0.87 in	3/4-16 UNF	
17739	1.56 in	0.25 in	1.00 in	0.75 in	1.93 in	0.37 in	1/4-28 UNF	
17740	2.44 in	0.50 in	1.50 in	1.31 in	3.09 in	0.62 in	1/2-20 UNF	
17741	2.87 in	0.62 in	1.75 in	1.75 in	3.75 in	0.75 in	3/4-16 UNF	
17742	4.12 in	1.00 in	2.12 in	2.75 in	5.50 in	1.37 in	1-12 UNF	
26007	4.12 in	1.00 in	2.12 in	2.75 in	5.50 in	1.37 in	1-14 UNS	
17747	4.12 in	1.00 in	2.12 in	2.75 in	5.50 in	1.37 in	1-12 UNF	
17743	4.12 in	1.25 in	2.12 in	2.75 in	5.50 in	1.09 in	1 1/4-12 UNF	
17744	5.37 in	1.50 in	3.00 in	3.50 in	7.12 in	1.31 in	1 1/2-12 UNF	
Stainless Steel								
33506	1.94 in	0.37 in	1.25 in	1.00 in	2.43 in	0.50 in	3/8-24 UNF	
33505	1.56 in	0.25 in	1.00 in	0.75 in	1.93 in	0.37 in	1/4-28 UNF	
33507	2.44 in	0.50 in	1.50 in	1.31 in	3.09 in	0.62 in	1/2-20 UNF	
33508	2.87 in	0.62 in	1.75 in	1.75 in	3.75 in	0.75 in	3/4-16 UNF	

# **Connecting Links**





# **Standard Features**

• Drop-forged carbon steel, heat-treated, hot-dipped galvanized finish

# Part Number/Price

Part#	A	В	С	D	Е	Safe Load*	Price
17794	1.50 in	1.00 in	0.43 in	0.87 in	0.25 in	1,325 lb	Consult
17795	2.06 in	1.37 in	0.56 in	1.12 in	0.37 in	2,750 lb	Consult
17797	3.31 in	2.09 in	0.78 in	1.81 in	0.62 in	7,250 lb	Consult
17798	3.87 in	2.50 in	0.93 in	2.12 in	0.75 in	10,250 lb	Consult
17799	5.00 in	3.31 in	1.25 in	2.75 in	1.00 in	15,500 lb	Consult

\*Do not exceed the safe load