



- Ethernet wireless bridge
- 5 GHz operating frequency
- RJ45 network interface
- PoE 2-pair (4, 5+; 7, 8 return) power method
- 24 V, 0.3 A gigabit PoE supply included
- 22 to 27 VDC voltage range
- Temperature: -40 °F to 158 °F (-40 °C to 70 °C)
- Humidity: 5% to 95% non-condensing

### Part Number/Price

Part #	Description	Price
204477	Nanostation	Consult

## Visible Lights and Audible Alarms



Blue strobe  
(reference photo only)

Product may vary from photo



Buzzer  
(reference photo only)

### Part Number/Price

Part #	Description	Price
<b>Visible Lights and Audible Alarms</b>		
22838	Buzzer, 80 dB, steady	Consult
22839	Buzzer, 80 dB, pulse	Consult
156106	Buzzer box, 115 VAC, FRP enclosure	Consult
43931	Strobe lights, red	Consult
43930	Strobe lights, amber	Consult

## Manual Pushbuttons/Pushbutton Switches



- Key switches
- Lighted pushbuttons
- Pilot lights
- Two- and three-position switches
- Colored pushbuttons
- Emergency stop mushroom switches
- Custom legend plates

### Part Number/Price

Part #	Description	Price
<b>Manual Pushbuttons/Pushbutton Switches</b>		
Consult	Operator and contact block combinations	Consult