RoughDeck® HP High Performance Low-Profile Floor Scale



Specifications

Warranty:

RoughDeck HP weldment five-year limited, load cells two-year limited, all other components one-year limited warranty

Standard Features

- · Heavy duty industrial design
- · Structural steel channel frame
- Four RL35N nickel-plated, IP66, OIML C3 shear beam load cells
- 6 m SURVIVOR® EL147HE hostile environment load cell cable to connect junction box to indicator
- Top-access junction box
- Rugged diamond safety treadplate deck
- Four adjustable stainless steel leveling feet
- Threaded eyebolt holes for easy lifting

Approvals









Additional models are available with the approvals shown here Please consult the factory for part numbers.

Part Number/Price

Part #	Size (W x L x H)	Capacity x Readability	Price
With Quick Connector			
162706	1.500 x 1.500 x 108 mm	1.500 kg x 500 g	Consult
162707	1.500 x 1.500 x 108 mm	3.000 kg x 1.000 g	Consult
162708	1.500 x 1.500 x 108 mm	6.000 kg x 2.000 g	Consult
162709	1.500 x 1.250 x 108 mm	1.500 kg x 500 g	Consult
162710	1.500 x 1.250 x 108 mm	3.000 kg x 1.000 g	Consult
162711	1.500 x 1.250 x 108 mm	6.000 kg x 2.000 g	Consult
162712	1.250 x 1.250 x 108 mm	1.500 kg x 500 g	Consult
162713	1.250 x 1.250 x 108 mm	3.000 kg x 1.000 g	Consult
162714	1.250 x 1.250 x 108 mm	6.000 kg x 2.000 g	Consult

Options/Accessories

Part #	Description	Price
19352	RoughDeck floor stand for indicator, 920 mm high, mild steel	Consult
126384	RoughDeck floor stand for indicator, 1.220 mm high, mild steel	Consult
N/A	Installation, testing, configuration and verification	Consult factory