

LEGAL FOR TRADE GF-P Series

Standard Features

- Pill-counting feature also complies with Handbook 44 requirements
- Fast, Super Hybrid Sensor (SHS) gives you the ultimate in response speed; just one second
- GLP/GMP/ISO compliance
- WinCT[®] communication tools software included
- Weighing chamber
- Tough die-cast aluminum housing
- Removable stainless steel pan 5 in x 5 in (127 mm x 127 mm)
- NTEP Certified and Pharmacopoeia approved
- IP54 splash proof operator keyboard protects against dust and spills, stainless steel weigh pan
- Data memory function
- Vacuum Fluorescent Display (VFD)
- RS-232 interface for connecting to printer or PC

Specifications

Weighing Units

Gram, Ounce, Pound, Pound/Ounce, Troy Ounce, Grain, Pound/Ounce (See technical manual for complete listing)

Operating Modes

Weigh, Count and Percent

Power

110/220V VAC adapter

Stabilization Time

Approx. 1 second (typical in FAST mode)

Decimal Ounce

GF-200P: 7.40755 x 0.00005 oz
GF-300P: 10.93493 x 0.00005 oz

Calibration Weight

GF-200P, GF-300P: 200 g

Operating Temperature

41° F to 104° F (5° C to 40° C)

Est. Weight

11 lb (5.2 kg)

Warranty

Five-year limited warranty

Return Policy

A&D Weighing Standard Policy - restock fee may apply

Approvals

NTEP CC 04-077 e=0.01g



Model	Capacity	Readability	Repeatability	Linearity	Weighing Chamber	Pan Size	Dimensions	Part #	List Price
GF-200P	210 g	0.001 g	0.001 g	±0.002 g	92 mm (3.6 in H)	127 mm (5 x 5 in)	210 x 317 x 86 mm (8.27 x 12.48 x 3.39 in)	97799	Consult
GF-300P	310 g	0.001 g	0.001 g	±0.002 g	92 mm (3.6 in H)	127 mm (5 x 5 in)	210 x 317 x 86 mm (8.27 x 12.48 x 3.39 in)	97800	Consult

Options/Accessories

Part #	A&D Model #	Description	Price
102891	GX-02	USB option	Consult
97697	GX-10	Glass breeze break for GF-200 and 300	Consult
97703	AX:073003691-S	Protective in-use cover for GF-200/300 (each)	Consult
97649	TB:648	AC adapter (120 V/220 V) standard with unit	Consult

