SURVIVOR RL2100 HE

Heavy-capacity Weigh Module Kits




Picture is a representation of actual product.


Order Information


Load Rating (Per Module)	Part#	Price
Single Module (Includes Load Cell)		
20,000 lb	32951	Consult
25,000 lb	65541	Consult
35,000 lb	32952	Consult
50,000 lb	32953	Consult
60,000 lb	32954	Consult
75,000 lb	32955	Consult
100,000 lb	32956	Consult
3-Module Kit		
20,000 lb	32970	Consult
25,000 lb	65984	Consult
35,000 lb	32969	Consult
50,000 lb	32968	Consult
60,000 lb	32967	Consult
75,000 lb	32966	Consult
100,000 lb	32965	Consult
4-Module Kit		
20,000 lb	32964	Consult
25,000 lb	65983	Consult
35,000 lb	32963	Consult
50,000 lb	32962	Consult
60,000 lb	32961	Consult
75,000 lb	32960	Consult
100,000 lb	32959	Consult

Dimensions

Rated Capacity	С	Н	H1	H2	L	L1	L2	L3	W	W1	W2	W3
lb/in												
20,000 to 25,000	0.78	6.85	0.75	0.75	10.00	6.00	8.00	7.50	8.00	6.00	6.00	8.00
35,000 to 100,000	1.13	9.42	1.00	1.00	14.00	6.50	9.00	11.50	10.00	7.50	6.50	9.00







Complete Kit Includes

- Three or four RL2100 HE stainless steel compression mounts with NTEP Certified RL75060S or RL75058S-LP stainless steel, welded seal double-ended beam load cells
- One JB4SS NEMA Type 4X stainless steel signal-trim junction box
- 25 ft of our hostile environment EL147HE SURVIVOR load cell cable

Standard Features

- NTEP Certified load cells, 5,000 d, Class IIIL/10,000 d, Class IIIL multiple cell
- · All stainless steel construction
- · Bolt-in-place design; module bolts directly to tank leg without requiring additional load buttons or mounting plates
- Self-checking design with lift-off/tip-over protection

Applications

- · Heavy-capacity tanks, blenders, reactors and bulk inventory management
- · Petroleum refining process control
- · Blending/batching

Load Cell Approvals



