

HIGH CAPACITY

GX-L Series

Standard Features

- IP65 protecton
- Internal adjustment weight with manual, interval or auto-environmental compensation
- RS-232 interface for connecting to printer or PC
- Data-collection software
- Auto re-zero function
- Flexible display positions
- Time and date
- Bright blue, fluorescent display
- Adjustable swing arm display
- Die-cast aluminum body with stainless weighing pan
- Detached digital weight indicator (KS models only)

Specifications

Weighing Units:

Carat, pennyweight, troy ounce, grain, decimal ounce, decimal pound, pound/ounce

Operating Modes:

Counting, percentage

Power:

Approx. 30 VA (supplied to the AC adapter)

Stabilization Time:

Approx. 1.5 seconds (typical in FAST mode)

Height with Column:

652 mm

Temperature:

Operating:
41 °F to 104 °F (5 °C to 40 °C)

Humidity:

RH less than 85% (no condensation)

Est. Weight:

Approx. 39.7 lb (18 kg)

Warranty:

Five-year limited

Return Policy:

A&D Weighing standard policy - restock fee may apply

Model	Capacity	Readability	Repeatability	Linearity	Pan Size	Dimensions	Part #	List Price
GX-12001L	12 kg	0.1 g	0.1 g	±0.2 g	15.2 × 13.5 in (386 × 343 mm)	14.6 × 24.2 × 5.1 in (372 × 615 × 130 mm)	227355	Consult
GX-22001L	22 kg	0.1 g	0.1 g	±0.2 g	15.2 × 13.5 in (386 × 343 mm)	14.6 × 24.2 × 5.1 in (372 × 615 × 130 mm)	227356	Consult
GX-32001LD	6.2 kg	0.1 g	0.1 g	±0.2 g	15.2 × 13.5 in (386 × 343 mm)	13.5 × 17.4 × 5.5 in (344 × 442 × 139 mm)	227357	Consult
GX-42001L	42 kg	0.5 g	0.5 g	±1 g	15.2 × 13.5 in (386 × 343 mm)	14.6 × 24.2 × 5.1 in (372 × 615 × 130 mm)	227358	Consult
GX-102000L	102 kg	1 g	1 g	±2 g	15.2 × 13.5 in (386 × 343 mm)	14.6 × 24.2 × 5.1 in (372 × 615 × 130 mm)	227359	Consult

Options/Accessories

Part #	A&D Model #	Description	Price
97607	AD-1682	Rechargeable battery pack	Consult
97608	AD-8920	Universal remote display	Consult
97813	GP-04	Comparator output with buzzer	Consult
97814	GP-06	Analog output (replaces standard RS-232C)	Consult
97815	GP-07	GP extension cable (factory installed 120 day lead time)	Consult
97816	GP-20	Underhook GP-12 kg thru 40 kg	Consult
97817	GP-21	Underhook GP-60 kg thru 102 kg	Consult
97605	AD-100-2	Anti-theft device	Consult
97820	07:3004753	Protective in-use cover	Consult
97613	TB:136	AC adapter (120 V) standard with unit	Consult
97614	TB:137	AC adapter (220 V)	Consult
97609	AD-8922	Remote controller	Consult
102904	GP-12	Animal weighing pan	Consult
151247	AD-1688	Data logger	Consult
97612	SW:128	Foot switch	Consult
196128	AD-8127	Impact dot matrix, statistical printer, includes cable	Consult

