MSI-4260M Port-A-Weigh

Industrial Crane Scale



Standard Features

- LCD display
- IP66 cast aluminum
- Top lifting eye or shackle with Crosby® (or equivalent) 360° thrust -bearing swivel hook
- Battery operated, six (6) D cell 1.5V alkaline batteries or 12 volt rechargeable battery (115/230 VAC battery charger is included)

Options

(Contact MSI for application consultation)

- · Rugged Remote
- RF modem install for connectivity to MSI-8000, MSI-8000HD RF, MSI-8004HD RF remote display, TranSend™ and LaserLight2™ remote display
- Wi-Fi communication available for specialty applications
- Substitute bottom swivel hook with shackle
- · Oversized top lifting eye or shackle
- · Oversized bottom hook
- Universal direct power supply; 85 to 265 VAC, 47 to 440 Hz/130 to 300 VDC
- · Low headroom top adapter
- · Audible alarm
- · Custom top and bottom interfaces

Approvals



Measuremen Canada Approved

Part Number/Price

Part #	Description	Resolution	Est. Weight	Price
Battery				
201951	500 lb (250 kg) with 12V battery F/A	0.2 lb (0.1 kg)	53 lb	Consult
201953	2,000 lb (1,000 kg) with 12V battery F/A	1.0 lb (0.5 kg)	53 lb	Consult
201954	5,000 lb (2,500 kg) with 12V battery F/A	1.0 lb (0.5 kg)	62 lb	Consult
201955	10,000 lb (5,000 kg) with 12V battery F/A	2.0 lb (1.0 kg)	62 lb	Consult
201956	20,000 lb (10,000 kg) with 12V battery F/A	5.0 lb (2.0 kg)	105 lb	Consult
201957	30,000 lb (15,000 kg) with 12V battery F/A	10 lb (5.0 kg)	125 lb	Consult
201958	50,000 lb (25,000 kg) with 12V battery F/A	10 lb (5.0 kg)	235 lb	Consult
201959	70,000 lb (35,000 kg) with 12V battery F/A	20 lb (10 kg)	270 lb	Consult
201960	100,000 lb (50,000 kg) with 12V battery F/A	20 lb (10 kg)	420 lb	Consult
D-Cell Batter	у			
201999	500 lb (250 kg) with D-cell battery F/A	0.2 lb (0.1 kg)	53 lb	Consult
202000	2,000 lb (1,000 kg) with D-cell battery F/A	1.0 lb (0.5 kg)	53 lb	Consult
202001	5,000 lb (2,500 kg) with D-cell battery F/A	1.0 lb (0.5 kg)	62 lb	Consult
202002	10,000 lb (5,000 kg) with D-cell battery F/A	2.0 lb (1.0 kg)	62 lb	Consult
202003	20,000 lb (10,000 kg) with D-cell battery F/A	5.0 lb (2.0 kg)	105 lb	Consult
202004	30,000 lb (15,000 kg) with D-cell battery F/A	10 lb (5.0 kg)	125 lb	Consult
202005	50,000 lb (25,000 kg) with D-cell battery F/A	10 lb (5.0 kg)	235 lb	Consult
202006	70,000 lb (35,000 kg) with D-cell battery F/A	20 lb (10 kg)	270 lb	Consult
202007	100,000 lb (50,000 kg) with D-cell battery F/A	20 lb (10 kg)	420 lb	Consult

Capacities over 70,000 lb are not NTEP and capacities over 20,000 lb are not currently Measurement Canada

Specifications

Power:

Battery operated, six (6) D cell 1.5 V alkaline batteries or 12 V rechargeable battery (115/230 VAC battery charger is included)

Resolution:

Max NTEP Approved Class III: 2,500 d Max NTEP Approved Class IIIL: 5,000 d Max Non-NTEP Approved: 10,000 d

Accuracy:

 $\pm 0.1\%$ +1 d of applied load

Annunciators:

COZ, battery level, net, total, lb/kg, stability, RF and setpoint LEDs

Display:

Five-digit, 1.75 in (44.5 mm) LCD with programmable brightness control

Displayable Units:

Pounds or kilograms select able

Keys/Buttons:

Power: Turns unit on or off

Zero: Zeros applied load up to 100% of capacity (limited range in NTEP configuration)

Tare: Tares applied load and displays weight in Net mode

User: Programmable as test, total, unit, peak hold, net/gross, view total and print

Temperature:

Certified: 14 °F to 104 °F (-10 °C to 40 °C) Operating: -20 °F to 122 °F (-28 °C to 50 °C)

Rating/Material:

IP66 cast aluminum

Design Overload:

200% Safe / 500% Ultimate (except where noted)

Operating Time:

Six (6) D Cell 1.5V alkaline batteries:

Up to 1,000 hours of battery life with typical use, less with RF modem

12 volt rechargeable battery: Up to 250 hours between charging with typical use, less with RF modem

Auto-Off Mode:

Powers off after the scale is not used for the set time (in minutes); 15, 30, 45, 60 or OFF selectable

Auto Sleep Mode:

Power down during non-use after the set time (in minutes) and powers up with weight change or any key press; 5, 15, 30 or OFF selectable

Service Counters:

Counts number of lifts over percentage of capacity and lifts over capacity

Filtering:

OFF, LO, HI-1 or HI-2 selectable

Radio Link:

802.15.4 at 2.4 GHz

Radio Effective Range:

Typically 100 to 300 ft line of sight

Warranty:

One-year limited

Approvals:

NTEP 19-122: 500 to 70,000 lb Measurement Canada AM-6198: 500 to 5,000 lb Measurement Canada AM-6249: 10,000 to 20,000 lb

^{*}Please review the Overhead Weighing Safety Guide

MSI-4260M Port-A-Weigh Industrial Crane Scale

Options/Accessories

Part #	Description	Est. Weight	Price
150971	MSI RF modem option kit (used in MSI-4260, MSI-4260M, MSI-9600HT)	-	Consult
139381	MSI-8000 RF remote display (requires MSI-4260M with RF modem)	5 lb	Consult
173014	RF Rugged Remote control (requires MSI-4260M with RF modem)	3 lb	Consult
153591	MSI-8000HD remote display, AC power and tilt bracket option (requires MSI-4260M equipped with RF modem)	3 lb	Consult
178281	MSI-8004HD AC, red/green 85~264 VAC, 47~440 Hz, 120~370 VDC	-	Consult
159221	Universal crane scale transport cart	180 lb	Consult
178004	LaserLight2, 4 in (100 mm) six-digit RF scoreboard (requires MSI-4260M equipped with RF modem)	21 lb	Consult
178006	LaserLight2, 6 in (150 mm) six-digit RF scoreboard (requires MSI-4260M equipped with RF modem)	37 lb	Consult
176956	Wi-Fi modem option kit (used in MSI-4260, MSI-4260M, MSI-6360, MSI-9600HT)	-	Consult
219297	Retrofit kit	-	Consult
Accessories			
150367	Battery assembly, 12V rechargeable	7 lb	Consult
138006	Universal 115/230 VAC, 50/60 Hz battery charger (NA plug standard)	4 lb	Consult
138007	Universal 115/230 VAC, 50/60 Hz battery charger (UK plug standard)	4 lb	Consult
138008	Universal 115/230 VAC, 50/60 Hz battery charger (EC plug standard)	4 lb	Consult
149549	Universal 115/ 230 VAC 50/60 Hz (NA plug standard) battery charger for MSI-8000 remote display	3 lb	Consult
Sub Hook w			
Consult	500 to 10,000 lb, 6.5 ton shackle	-	Consult
Consult	20,000 to 30,000 lb, 17 ton shackle	-	Consult
Consult	50,000 lb, 25 ton shackle	-	Consult
Consult	70,000 lb, 40 ton shackle	-	Consult
Consult	100,000 lb, 55 ton shackle	-	Consult
	ting Eye/Shackle		
Consult	500 to 10,000 lb capacity	-	Consult
Consult	20,000 to 30,000 lb capacity, adapter with 25 ton shackle	-	Consult
Consult	50,000 to 70,000 lb capacity	-	Consult
Consult	100,000 lb capacity	-	Consult