

Uni-9 RP pictured with remote scale base and optional wrap station components. (47670, 47672,53962)

# **Specifications**

# Capacity:

 $60 \times 0.01$  lb

#### **Print Speed:**

3.9/ 4.7/ 5.9 in/sec (100/ 120/ 150 mm/sec)

#### Label Size:

Width: 1.2 to 3 in (30 to 80 mm) Length: 0.8 to 7.9 in (20 to 200 mm)

#### Display:

Operator side: 12 in (800 × 600) color touch panel Uni-9 DB: 8.4 in Customer side: not available Type: Five-wire resistive

### **Display Items:**

Tare: Four-digits Unit price: Six-digits Weight: Five-digits Total price: Six-digits

# **Rear Display:**

Not available

## Memory:

SSD memory 250MB

### **Communications:**

Static or DHCP TCP/IP 1G Base T Ethernet auto-duplex Wireless WEP/WPA/WPA2

### Input/Output:

LAN 1 channel USB 4 channel SD 1 channel (SDHC: max 32 GB) (for transaction data)

### **Operating Voltage:**

Range: 100 to 240V, 50/60Hz Permissible tolerance: +/- 10%

#### **Operating Environment:**

32 °F to 104 °F (0 °C to 40 °C) 20% to 85% relative humidity

# Power Supply:

AC 100 to 240V, 50/60 Hz

#### **Power Consumption:**

Stand-by: 50W In operation: 120W

### Classification:

NTEP CC 12-121 UL listed

#### Warranty:

One-year limited



# Ishida Uni-9 RP

PC-based Price Computing Printer with Color Touchscreen and Remote Scale Platform

The Uni-9 RP with a standard 60lb capacity remote base, in conjunction with a wrapping station, is capable of weighing and labeling non-standard sizes and shapes with the same presentation as fully automatic wrappers. The PC-based Uni-9 RP platform communicates with PCs via Ethernet or Wi-Fi.


# **Standard Features**

- Large color touchscreen (12 in)
- · Adjustable touchscreen viewing angle
- $60 \times 0.01$  lb single-range weighing
- · Front-load label cassette
- Ethernet communications
- · SD memory card slot
- SSD memory 250 MB
- 30+ selectable fixed bar code formats
- Compatible with third-party communication software, including ADC's InterScale, Invatron's PLUM and Droste's PCScale Manager
- 80 mm wide printing
- Up to 150 mm/sec print speed
- 2020 nutrition labeling
- Configurable for different languages including Spanish, French and German

PART #	MODEL	WIRELESS	CAPACITY
160266	Uni-9 RP scale with internal RF	√	0-60 lb x 0.01 lb
188728	Uni-9DB XL, no customer display		0-60 lb x 0.01 lb


Please refer to the labels section of this catalog for ordering information and case quantity pricing.

DIMENSIONS 60LB BASE				
A	15.4 in (390 mm)	D	12.0 in (305 mm)	
В	10.6 in (270 mm)	Е	7.9 in (200 mm)	
С	4.9 in (125 mm)			




60lb Base

DI	DIMENSIONS				
Α	11.9 in (302 mm)	G	11.8in (300 mm)		
D	6.2 in (158.5 mm)	Н	5.6 in (141 mm)		
Е	5.8 in (147.5 mm)	■ 6.5 in (166 mm			
F	20.3 in (516 mm)	J	2.2 in (55 mm)		



Uni-9 indicator



# Ishida Uni-9 RP

PC-based Price Computing Printer with Color Touchscreen and Remote Scale Platform

PART #	MODEL/DESCRIPTION	WIRELESS	CAPACITY	EST. SHIPPING WEIGHT	PRICE
160266	Uni-9 RP scale with internal RF		0-60 lb x 0.01 lb	47 lb	Consult
188728	Uni-9DB XL, no customer display		0-60 lb x 0.01 lb	45 lb	Consult

# **Options/Accessories**

155393	Additional label cassette	Consult
159947	Linerless label cassette	Consult
47670	Wrap station base, (W x D x H) 22 x 23 x 32 in	Consult
47672	Wrap station left wing, (W x D) 14 x 22 in	Consult
46927	Wrap station right wing, (W x D) 14 x 22 in	Consult
53962	Wrap station right wing with hood, (W x D) 14 x 34 in	Consult
53963	Wrap station all-purpose center shelf, (W x D) 24 x 15 in	Consult
104948	Scale base alignment plate	Consult
155176	Day Glow label dispenser for PN 47670	Consult
151761	Day Glow label dispenser spacer, pack of ten	Consult
174110	SD memory card, 2 GB	Consult

### Communication

160259**	ScaleLink Pro 5 software CD, license file required and purchased separately (see page 72)	Consult
152628*	ScaleLink Pro 5 license file, one license required per machine	Consult
78860	Crossover cable, Ethernet CAT5, 6ft	Consult
174172	Internal wireless communication 802.11 b/g 2.4 Ghz	Consult

# **Manuals and Service Tools**

118188**	Uni Series support USB (contains manuals, training videos and libraries)	Consult
160906	USB flash memory, 1 GB	Consult
162196**	Service manual, hardware	Consult
162199**	Service manual, programming	Consult
162299**	Installation manual	Consult

# **Label Stock**

Please refer to labels section of this catalog for ordering information and case quantity pricing.

<sup>\*\*</sup>Manuals and software programs can be downloaded from the distributor section of www.ricelake.com/retail.



Uni-9 RIP pictured with remote scale base and optional wrap station components. (47670, 47672,53962)

<sup>\*</sup>Software key is provided after online registration is completed