

# CLS Series Class III

Forklift Scale



## Standard Features

### Scale Carriage

- 38 in, 8,000 × 5 lbs, non-NTEP
- 1-1/2-in thick front and back painted steel plates coupled by four flexures
- Top cleats are welded, pinned and bolted
- Welded centering pin
- Two 5,000-lb S-beam load cells
- iQUBE<sup>2</sup>® junction box with inclinometer
- Molded coiled cable, up to 15 ft uncoiled

### Presale Requirements

- Provide completed forklift questionnaire for quotation
- Compatible with most Class III forklift attachments, consult factory

### Installation Recommendations

- When installing a forklift scale, OSHA requires the end user to de-rate the lift capacity of the forklift

## Options

- CLS-680, 18 to 72 VDC
- Virtui<sup>3</sup>
- Mobile printer

## Specifications

### Warranty:

Two-year limited

## Part Number/Price

Part #	Capacity	Description	Est. Weight	Price
<b>Class III, CLS-680, Non-NTEP Certified</b>				
212521	8,000 × 5 lb	38 in W, 20 in H forklift carriage, 9 to 36 VDC	985 lb	Consult
214092	8,000 × 5 lb	38 in W, 20 in H forklift carriage, 9 to 36 VDC, cableless	990 lb	Consult
<b>Class III, CLS-920i, Non-NTEP Certified</b>				
219975	8,000 × 5 lb	38 in W, 20 in H forklift carriage, 9 to 36 VDC	990 lb	Consult
214093	8,000 × 5 lb	38 in W, 20 in H forklift carriage, 9 to 36 VDC, cableless	1,005 lb	Consult

For indicator drawings and dimensions, please see page 410 and page 411  
For scale drawings and dimensions, visit [www.ricelake.com](http://www.ricelake.com).