

# CW-90B

Light-capacity Bench Scale



## Standard Features

- IP67 aluminum environmentally sealed load cell
- 304 stainless steel construction
- Meets HACCP requirements
- Five-point overload protection
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces

## Specifications

**Load Cell, NTEP Certified:**  
IP67 aluminum, environmentally sealed

**Output Impedance:**  
350 ohm

**Maximum Overload:**  
180% to 200% depending on capacity

**Overload Protection:**  
Five-point, independently adjusted

**Scale Frame:**  
AISI304L, straight line finish, Ra= 45 +/- 10

**Scale Cover:**  
AISI304L, straight line finish, Ra= 45 +/- 10

**Cable Length:**  
34 in or 10 ft

**Compensated Temperature Range:**  
14 °F to 104 °F (-10 °C to 40 °C)

**Warranty:**  
Two-year limited

**Approvals:**  
NTEP 95-072, Class III 5,000 d  
Measurement Canada AM-5082  
NSF  
Load cell is cMus Approved

## Approvals



## Part Number/Price

Part #	Platform Capacity	Dimensions (L x W x H)	Est. Weight	Price	
<b>10 ft cable</b>	<b>34 in cable</b>				
<b>112599</b>	<b>106137</b>	5 lb (2.5 kg)	10 x 10 x 4.25 in	14 lb	Consult
<b>112601</b>	<b>106138</b>	10 lb (5 kg)	10 x 10 x 4.25 in	14 lb	Consult
<b>112603</b>	<b>106139</b>	25 lb (10 kg)	10 x 10 x 4.25 in	14 lb	Consult
<b>112605</b>	<b>106140</b>	25 lb (10 kg)	12 x 12 x 4.25 in	17 lb	Consult
<b>112607</b>	<b>106141</b>	50 lb (25 kg)	12 x 12 x 4.25 in	17 lb	Consult
<b>112609</b>	<b>106142</b>	100 lb (50 kg)	12 x 12 x 4.25 in	17 lb	Consult

## Options/Accessories

Part #	Description	Catalog Page #
Consult	Scale columns	See page 204
Consult	Ball transfer and roller conveyor scale tops	See page 203
Consult	Mobile scale carts	See page 199 to page 202

## Dimensions

CW-90B			
10 x 10 in			
A	4.25 in	C	10.00 in
B	10.00 in	C1	10.25 in
B1	10.25 in		

Note: 1 in = 25.4 mm

12 x 12 in			
A	4.25 in	C	12.00 in
B	12.00 in	C1	12.25 in
B1	12.25 in		

Note: 1 in = 25.4 mm

