# **DTL Plus/DTT**



Not recommended for applications with exposure to sunlight, fluorescent lamps or heat

#### **Standard Features**

### DTL Plus/DTT

- Top-coated white matte finish
- Requires a visible light (633 nm) scanning device for barcodes
- Withstands some contact with alcohol, blood, grease and water

## Part Number/Price

Part #	Description	Price
109340	3 in wide continuous tag stock, 7.2 mil, 3 in core, 8 in O.D., 480 ft wound out	Consult
109298	4 in wide continuous tag stock, 7.2 mil, 3 in core, 8 in O.D., 480 ft wound out	Consult
119829	5 in wide perforated, two up, fan folded stacks of 1,000	Consult each

# **DTL-SYN**

Direct Thermal Label



DTL-SYN

Direct Thermal Synthetic Label

# **Standard Features**

## **DTL-SYN**

- Top-coated white matte finish
- Requires a visible light (633 nm) scanning device for barcodes
- All-temperature permanent acrylic adhesive with short repositioning time
- Withstands some contact with alcohol, blood, grease and water

#### Part Number/Price

Part #	Description	Price
109448	3.25 × 3.25, 3 in core, 8 in O.D., 1,800 LPR, wound out, 208 roll minimum order	Consult/roll