

# EPSON® TM-T88VI

Direct Thermal POS Receipt Printer



## Standard Features

- High-speed printing of both text and graphics
- True grayscale image printing
- Convenient drop-in paper loading, auto cutter and status LEDs
- ENERGY STAR® qualified
- Accommodates 58 mm or 80 mm paper roll
- Paper saving print features
- Improved cover protects from dust and debris
- OS support for Microsoft® Windows® 7, Vista, XP, 2000; Mac OS X v10.4, v10.5, v10.6 (Power PC/ Intel Processor) and Linux

## Specifications

### Print Speed:

300 mm/s (11.81 inch/s)

### Interface:

Built-in USB and serial interface (DB-25F);  
built-in USB and Ethernet; or built-in USB

### Paper Dimensions:

80 mm: 3.13 × 3.27 in diameter  
58 mm: 2.26 × 3.27 in diameter

### Paper Thickness:

55 to 80 µm

### Power:

24 VDC ± 7%

### Temperature:

Operating: 31 °F to 113 °F (5 °C to 45 °C)  
Storage: 14 °F to 122 °F (-10 °C to 50 °C)

### Reliability:

MTBF: 360,000 hours  
MCBF: 70 million lines

### Dimensions:

(L x W x H)  
7.68 × 5.71 × 5.83 in  
(195 × 145 × 148 mm)

### Warranty:

One-year limited

## Part Number/Price

| Part # | Description                                  | Est. Weight | Price   |
|--------|--|-------------|---------|
| 117233 | TM-T88V, RS-232 and USB, PS-180 power supply | 4 lb        | Consult |

## Options/Accessories

| Part #  | Description   | Price   |
|---------|---|---------|
| 23112   | Power supply, PS-180  | Consult |
| 69917   | One-ply thermal, (W) 3.125 in (75.44 mm, 2.97 in dia.) 7/16 core 230 ft     | Consult |
| 83007   | Parallel option connect-it cartridge  | Consult |
| 15568   | 25-pin D-sub male to 25-pin D-sub male RS-232 serial interface cable        | Consult |
| 15547   | Blunt end, 25-pin D-sub male RS-232 serial interface (Rice Lake indicators) | Consult |
| Consult | Custom RS-232 serial cable  | Consult |
| 79074   | USB-A (male) to USB-B (male) cable, 6 ft                                    | Consult |
| 167545  | TM88IV and V printhead  | Consult |

PRINTERS