

# Explorer® Series

## Standard Features

- Automatic calibration via AutoCal™
- Communication RS-232C
- On-screen prompts
- Spill channel
- Applications library
- Backlit, high-resolution dot matrix display
- GLP outputs via RS-232 to meet traceability requirements
- User-selectable filter, stability indicator and auto-zero tracking
- Five-language operation display text
- Protective in-use cover and security bracket
- Underweigh hook

## OPTIONS

- NTEP Certified, Legal for Trade models by special order

## Specifications

### Weighing Units:

Milligram, gram, kilogram, ounce, carat, pennyweight, troy ounce, grain, newton (see technical manual for complete listing)

### Operating Modes:

Weighing, percent weighing, parts counting, checkweighing, dynamic/animal weighing, filling, totalization, formulation, Differential weighing, density determination, peak hold, ingredient costing, pipette adjustment, SQC

### Power:

AC adapter input: 100 to 240 VAC 0.6 A 50/60 Hz

### Stabilization Time:

EX124: Approx. 2 seconds

EX224: Approx. 2 seconds

EX324: Approx. 3 seconds

### Calibration:

AutoCal™ at 1.5 °C temperature change, 11 hours, and external calibration

### Temperature:

Operating:

50 °F to 86 °F (10 °C to 30 °C)

### Est. Weight:

21.1 lb (9.6 kg)

### Warranty:

Two-year limited

### Return Policy:

OHAUS standard policy - restock fee may apply

Model	Capacity	Readability	Repeatability	Linearity	Weighing Chamber	Pan Size	Dimensions	Part #	List Price
<b>EX124</b>	120 g	0.0001 g	±0.0001 g	±0.0002 g	9.5 × 7.5 × 6.5 in (241 × 190 × 165 mm)	Ø 3.5 in (90 mm)	9.1 × 15.5 × 13.8 in (230 × 393 × 350 mm)	<b>121192</b>	Consult
<b>EX224</b>	220 g	0.0001 g	±0.0001 g	±0.0002 g	9.5 × 7.5 × 6.5 in (241 × 190 × 165 mm)	Ø 3.5 in (90 mm)	9.1 × 15.5 × 13.8 in (230 × 393 × 350 mm)	<b>121193</b>	Consult
<b>EX324</b>	320 g	0.0001 g	±0.0001 g	±0.0002 g	9.5 × 7.5 × 6.5 in (241 × 190 × 165 mm)	Ø 3.5 in (90 mm)	9.1 × 15.5 × 13.8 in (230 × 393 × 350 mm)	<b>121194</b>	Consult

## Options/Accessories

Part #	Model #	Description	Price
<b>35263</b>	80850043	Security device for EX	Consult
<b>77712</b>	80500524	RS-232 cable, PC 25-pin to EX	Consult
<b>70406</b>	80500525	RS-232 Cable, PC 9-pin to EX	Consult
<b>156234</b>	46001724	Multi-range AC adapter	Consult
<b>156235</b>	46001780	International plug set	Consult

