

NEW


Picture is a representation of actual product.

Approvals**Order Information**

Load Rating	Part #	Est. Weight	Price
25 lb	226878	2 lb	Consult
50 lb	226879	2 lb	Consult
100 lb	226880	2 lb	Consult
150 lb	226881	2 lb	Consult
250 lb	226882	2 lb	Consult
500 lb	226883	2 lb	Consult

Dimensions

Rated Capacity	A	B	C	D	E	F	G	H	I	J
lb/in										
25 to 500	2.81	1.30	0.62	0.26	0.25	0.50	1.81	1.00	1.00	0.50

**Interchangeable Products**

RICE LAKE WEIGHING SYSTEMS

RL50210.....page 120

RICE LAKE WEIGHING SYSTEMS

RL50219SS.....page 118

VPG® SENSORTRONICS®

60040.....page 286

ARTECH®

50210

VPG® REVERE

5503**Weigh Module Available**

RICE LAKE WEIGHING SYSTEMS

RL50210TA.....page 37**Specifications****Full Scale Output:**

300 mv/v

Output Resistance:

350 ohms

Input Resistance:

360 to 450 ohms

Material/Finish:

Alloy steel, nickel plated

Temperature:Operating:
0 °F to 150 °F (-18 °C to 65 °C)**Seal Type:**

Environmentally sealed, IP65

Safe Overload:

50% full scale

Rated Excitation:

5 to 10 VDC

Nonlinearity:

0.03% full scale

Hysteresis:

0.02% full scale

Insulation Resistance:

5,000 megohm

Deflection at Capacity:25 to 50 lb: 0.008 in
100 lb: 0.010 in
150 lb: 0.012 in
250 lb: 0.016 in
500 lb: 0.025 in**Cable Length:**

20 ft

Cable Diameter:0.200 in
Polyurethane jacket**Cable Color Code:**Red +Excitation
Black -Excitation
Green +Signal
White -Signal**Warranty:**

Two-year limited

Approvals:

cFMus

**RICE LAKE
LOAD CELLS**