

Summit® 3000

Low-profile Floor Scale

FLOOR SCALES



Approvals



Measurement
Canada
Approved

Part Number/Price

Part #	Size (W × L × H)	Capacity	Est. Weight	Price
Single Scale				
74715	3 ft × 3 ft × 3.625 in	2,000 lb	190 lb	Consult
74716	4 ft × 4 ft × 3.625 in	2,000 lb	305 lb	Consult
74717	4 ft × 4 ft × 3.625 in	5,000 lb	305 lb	Consult
74718	4 ft × 4 ft × 3.625 in	10,000 lb	305 lb	Consult
74719	4 ft × 5 ft × 3.625 in	5,000 lb	395 lb	Consult
74720	4 ft × 5 ft × 3.625 in	10,000 lb	445 lb	Consult
74721	4 ft × 6 ft × 3.625 in	5,000 lb	470 lb	Consult
74722	4 ft × 6 ft × 3.625 in	10,000 lb	525 lb	Consult
74723	5 ft × 5 ft × 3.625 in	5,000 lb	505 lb	Consult
74724	5 ft × 5 ft × 3.625 in	10,000 lb	575 lb	Consult
Single Scale—Measurement Canada Approved				
77440	3 ft × 3 ft × 3.625 in	1,000 kg	190 lb	Consult
77373	4 ft × 4 ft × 3.625 in	1,000 kg	305 lb	Consult
77346	4 ft × 4 ft × 3.625 in	2,500 kg	305 lb	Consult
77347	4 ft × 4 ft × 3.625 in	5,000 kg	305 lb	Consult
82880	4 ft × 5 ft × 3.625 in	2,500 kg	395 lb	Consult
82881	4 ft × 5 ft × 3.625 in	5,000 kg	445 lb	Consult
77348	5 ft × 5 ft × 3.625 in	2,500 kg	505 lb	Consult
77349	5 ft × 5 ft × 3.625 in	5,000 kg	575 lb	Consult

Options/Accessories

Part #	Description	Price
75819	Floor anchor plates, mild steel (set of two)	Consult
Consult	Top-access foot adjust holes	Consult
19352	Floor stand for indicator, 36.3 in high, mild steel	Consult
126384	Floor stand for indicator, 48 in high, mild steel	Consult

*For custom sizes or capacities, please consult factory for RoughDeck® HP pricing

Standard Features

- Four NTEP Certified alloy steel shear beam load cells
- Top access junction box
- Diamond safety tread plate deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2-20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable. The load cell cable exits weldment toward the interior of scale, allowing flexibility to route out any side of scale to digital weight indicator.

Specifications

End Load Capacity:

- 100% full scale at 2,000 lb and 5,000 lb
- 80% full scale at 10,000 lb

Cable Length:

- 20 ft (6.1 m) for connecting junction box to indicator

Threaded Eyebolt:

- Hole (1/2-20 NF) located in center of deck for easy lifting

Warranty (limited):

- Weldment and load cells: Two-years
- All other components: One-year

Approvals:

- NTEP 92-001A9, Class III 5,000 d
- Measurement Canada AM-5530, Class III 5,000 d (2,500 kg, 5,000 kg) 2,000 d (1,000 kg)