Valor® 1000 Series

Standard Features

- Removable stainless steel platform cover
- · Mid-profile ABS plastic housing
- · Front-mounted leveling device
- Compact footprint
- · Fast response time
- Easy to clean

Specifications

Weighing Units:

Gram, Kilogram, Ounce, Pound, Pound/Ounce

Operating Modes:

Weigh, Accumulate, Checkweigh

Power:

Universal AC adapter included (9 VDC 500 mA) Four D Cell alkaline batteries (not included)

Stabilization Time:

= 1.5 seconds

Scale Overload:

120% of capacity

Decimal Ounce:

V12P3: 105 oz × 0.02 oz V12P6: 210 oz × 0.05 oz V12P15: 520 oz × 0.1 oz V12P30: 1,058 oz × 0.5 oz

Decimal Pound:

V12P3: 6.6 lb × 0.001 lb V12P6: 13 lb × 0.002 lb V12P15: 33 lb × 0.01 lb V12P30: 66 lb × 0.02 lb

Grams:

V12P3: 3,000 g × 0.5 g V12P6: 6,000 g × 1 g V12P15: 15,000 g × 2 g V12P30: 30,000 g × 5 g

Operating Temperature:

32 °F to 104 °F (0 °C to 40 °C) at 10% to 95% relative humidity non-condensing, up to 2.5 miles/4,000 m above sea level

Est. Weight:

8.8 lb (4.0 kg)

Battery life:

1,500 hours (with/without backlight on)

Warranty:

One-year limited

Return Policy:

OHAUS standard policy - restock fee may apply

Approvals:

NSF



				1	l	
Model	Capacity	Readability	Pan Size	Dimensions	Part #	List Price
V12P3	3 kg	0.5 g	7.5 × 9.8 in (190 × 250 mm)	10.1 × 11 × 4.8 in (256 × 280 × 121 mm)	205019	Consult
V12P6	6 kg	1 g	7.5 × 9.8 in (190 × 250 mm)	10.1 × 11 × 4.8 in (256 × 280 × 121 mm)	205020	Consult
V12P15	15 kg	2 g	7.5 × 9.8 in (190 × 250 mm)	10.1 × 11 × 4.8 in (256 × 280 × 121 mm)	205021	Consult
V12P30	30 kg	5 g	7.5 × 9.8 in (190 × 250 mm)	10.1 × 11 × 4.8 in (256 × 280 × 121 mm)	205023	Consult

Options/Accessories

Part#	Model#	Description	Price			
97250	80250400	Stainless steel scoop 11.9 \times 7.4 \times 1.7 in (30 \times 18.7 \times 4.3 cm)	Consult			
100292	80250954	Stainless steel scoop 17.2 × 11 × 3.4 in (44 × 28 × 8.5 cm)	Consult			

