

Tripp-Lite USB to Serial Converter/Adapter

Serial Adapters



Standard Features

- Portable design—no AC power required
- Simple plug-and-play setup
- Supports data transfer rates of more than 500 kbps
- Hot swappable

Specifications

Data Transfer Rate:
More than 500 kbps

LED:
Data transfer/handshaking (orange)

Power Consumption:
450 Mw USB

Specifications:
V1.1 compliant


INDICATORS / CONTROLLERS

Part Number/Price


Part #	Description	Est. Weight	Price
178501	Adapter,USB Serial FTDI US232R-100, 3.28 ft, iDim Series for use with RLWS indicator and Postal Scales	-	Consult
153603	USB to serial converter	1 lb	Consult
22436	Cable DB9F to blunt end, 6 ft	1 lb	Consult

DB-9 PIN Assignments:

PIN	Assignment	PIN	Assignment
1	CD	6	DSR
2	RXD	7	RTS
3	TXD	8	CTS
4	DTR	9	RI
5	GND		



DB9 (Male) Connector



Type A USB Connector



USB to Serial Adapter

DB-9 PIN Assignments:

PIN	Assignment	PIN	Assignment
1	CD	6	DSR
2	RXD	7	RTS
3	TXD	8	CTS
4	DTR	9	RI
5	GND		