



Approvals



Measurement
Canada
Approved

Part Number/Price

Part #	Description	Capacity	Est. Weight	Price
115125	RPL-6S	6.00 × 0.002 lb	15 lb (6.3 kg)	Consult
115128	RPL-15S	15.00 × 0.005 lb	15 lb (6.3 kg)	Consult
115129	RPL-30S	30.00 × 0.01 lb	15 lb (6.3 kg)	Consult
115130	RPL-60S	60.00 × 0.02 lb	15 lb (6.3 kg)	Consult

Options/Accessories

Part #	Description	Price
108516	Rechargeable battery	Consult
108518	AC adapter 110-230 VAC, U.S. plug	Consult
129953	AC adapter, 110-230 VAC, Euro plug	Consult
115519	Additional operator guide	Consult

Standard Features

- Compact and easy to use
- IP68 water and dust resistant
- Stainless steel finish
- Removable weigh pan for quick and easy cleaning
- LED display
- AC adapter included
- Legal for Trade
- HACCP compliant

Options

- Rechargeable battery

Specifications

Display:

LED, six-digit

Capacity:

	Pound	Gram	Ounce
RPL-6S	6.0 × 0.002 lb	3,000 × 1 g	60.0 × 0.02 oz
RPL-15S	15.0 × 0.005 lb	6,000 × 2 g	150.0 × 0.05 oz
RPL-30S	30.0 × 0.01 lb	15,000 × 5 g	300.0 × 0.1 oz
RPL-60S	60.0 × 0.02 lb	30,000 × 10 g	600.0 × 0.2 oz

Annunciators:

Ounces, grams, pounds, net, center of zero, battery usage

Keyboard:

Rezero, tare, on/off, unit

Resolution:

Internal: 90,000 count

Display: 3,000

Humidity:

15 to 85% RH

Temperature:

Operating: 14 °F to 104 °F (-10 °C to 40 °C)

Power Consumption:

18 W when using DC power, 3 W when using rechargeable battery

Power Source:

AC 117/100 V, 240/230/220 V

DC 12 V/1.5 A, DC 6 V 5 Ah optional rechargeable battery

Optional Battery:

60 hours of continuous usage

Calibration:

RPL-S: Grams

Overall Dimensions:

(L × W × H)

11.4 × 9.9 × 5.3 in

(290 × 252 × 135 mm)

Package Size:

(L × W × H)

14.8 × 13.3 × 9.6 in

(377 × 337 × 245 mm)

Platter Size:

9.3 × 7.8 in

(237 × 198.0 mm)

Warranty:

One-year limited

Approvals:

NTEP 10-068, Class III 3,000 d

Measurement Canada AM-5794