

Ishida WIL-Acro II

Compact Labeler
with Color Touchscreen



RICE LAKE[®]
WEIGHING SYSTEMS

800-472-6703
www.ricelake.com

Ishida WIL-Acro II Compact Labeler with Color Touchscreen



Changing label rolls is simplified with a front loading label cassette.

The WIL-Acro II compact label printer features ultra-fast printing speeds and a front-loading label cassette. The color touchscreen streamlines operation and its compact size is ideal for applications with limited space, such as floral counters and bakeries.

Supporting multiple label formats, the WIL-Acro II prints all legally required ingredient and nutritional information. Productivity is also increased immensely with a label batching feature which accumulates and prints multiple labels for several different items. A full-color touchscreen, sleek design and custom label features make the WIL-Acro II an impressive solution for all versatile labeling needs.

Standard Features

- Color touchscreen user-interface with adjustable viewing angle
- Front-loading label cassette
- Prints all legally required ingredient and nutritional information
- Stores and prints graphics for custom labeling
- Ethernet communications
- Wireless communication 802.11 b/g
- Assign images to category, presets, or function keys
- SSD memory
- Compatible with third-party communication software, including Invatron's PLUM and ADC's InterScale
- 76mm wide printing
- Up to 150mm/sec print speed
- PC-based operating system
- Solid State hard drive
- SD memory card slot

Specifications

Display: 8.4in TFT color, with back light, 800 x 600 dots

DISPLAY ITEMS:

| | |
|-------------------------|---|
| Unit price: | Five digits |
| Total price: | Six digits |
| Images: | Categories, presets and function keys |
| Memory Capacity: | SSD memory 585MB |
| Communications: | Static TCP/IP 1G Base T Ethernet (auto duplex) wireless WEP WPA WPA2 |
| Input/Output: | LAN 1 channel, USB 4 channels |
| Print Head: | Direct thermal 3in (76mm) |
| Print Speed: | Up to 6in (150mm) per second |

LABEL SIZE:

| | |
|----------------|------------------------|
| Width: | 1/5 – 3.1in (30-80mm) |
| Length: | 1.2 – 7.9in (20-100mm) |

LABEL ROLL:

| | |
|--------------------------|-------------------|
| Inside diameter: | 1.6in (40mm) min |
| Outside diameter: | 3.9in (100mm) max |

LABEL BACKING PAPER:

| | |
|----------------------|-------------------------|
| Width: | Up to 3.3in (84mm) |
| Weight: | 24lbs |
| Power Supply: | AC110 to 120V, 60Hz, 4A |

POWER CONSUMPTION:

| | |
|------------------------|-----------|
| Standby: | 50W |
| In operation: | 120W |
| Classification: | UL listed |

OPERATING CONDITIONS:

| | |
|---------------------|-------------------------------|
| Temperature: | 32° F – 104° F (0° C – 40° C) |
| Humidity: | 20 – 85% (no condensation) |
| Warranty: | One-year limited warranty |

Your Rice Lake Weighing Systems distributor is:

RICE LAKE
WEIGHING SYSTEMS

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com

An ISO 9001 registered company © 2017 Rice Lake Weighing Systems PN 184297 8/17
Specifications subject to change without notice.